# Safety Data Sheet

Copyright,2026, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|---|---|---|---|
| **Document Group:** | 10-0286-4 | **Version Number:** | 36.02 |
| **Issue Date:** | 01/26/26 | **Supersedes Date:** | 09/29/25 |

## SECTION 1: Identification

**1.1. Product identifier**
3M™ Edge Sealer 3950

**Product Identification Numbers**

| ID Number | UPC | ID Number | UPC |
|---|---|---|---|
| 75-3472-1519-8 | 00051128820186 | 75-3472-6963-3 | 00051128949078 |

7000005295, 7010303382

**1.2. Recommended use and restrictions on use**

**Recommended use**
Edge Sealer for Screen Printing Inks and Graphic Films, Sealant

**1.3. Supplier's details**

| | |
|---|---|
| **MANUFACTURER:** | 3M |
| **DIVISION:** | Commercial Branding and Transportation Division |
| **ADDRESS:** | 3M Center, St. Paul, MN 55144-1000, USA |
| **Telephone:** | 1-888-3M HELPS (1-888-364-3577) |

**1.4. Emergency telephone number**
1-800-364-3577 or (651) 737-6501 (24 hours)

## SECTION 2: Hazard identification

**2.1. Hazard classification**
Flammable Liquid: Category 3.
Serious Eye Damage/Irritation: Category 2B.
Carcinogenicity: Category 2.
Reproductive Toxicity: Category 1B.
Specific Target Organ Toxicity (single exposure): Category 1.
Specific Target Organ Toxicity (repeated exposure): Category 1.
Specific Target Organ Toxicity (single exposure): Category 3.

**2.2. Label elements**
**Signal word**
Danger

**Symbols**
Flame |Exclamation mark |Health Hazard |

**Pictograms**



**Hazard Statements**
Flammable liquid and vapor.

Causes eye irritation.
Suspected of causing cancer.
May damage fertility or the unborn child.
May cause drowsiness or dizziness.
Causes damage to organs: sensory organs.

Causes damage to organs through prolonged or repeated exposure: nervous system.
May cause damage to organs through prolonged or repeated exposure: sensory organs.

**Precautionary statements**

**Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use explosion-proof electrical, ventilating and lighting equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Do not breathe vapors.
Wash exposed skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, eye protection, face protection, and if needed, respiratory protection (see SDS Section 8).

**Response:**
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Call a POISON CENTER or doctor.
Get medical attention if you feel unwell.
If eye irritation persists: Get medical advice.
In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**
Store in a well-ventilated place. Keep cool.
Store locked up.

**Disposal:**

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

48% of the mixture consists of ingredients of unknown acute oral toxicity.
48% of the mixture consists of ingredients of unknown acute dermal toxicity.
48% of the mixture consists of ingredients of unknown acute inhalation toxicity.

## SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---|---|---|
| Xylene | 1330-20-7 | 30 - 60 Trade Secret * |
| MODIFIED ACRYLIC RESIN | Trade Secret* | 30 - 60 |
| Ethylbenzene | 100-41-4 | 7 - 13 Trade Secret * |
| Toluene | 108-88-3 | 0.3 - 0.6 |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

**4.1. Description of first aid measures**

**Inhalation:**
Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**
Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If Swallowed:**
Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

**4.3. Indication of any immediate medical attention and special treatment required**
Not applicable

## SECTION 5: Fire-fighting measures

**5.1. Suitable extinguishing media**
In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**5.2. Special hazards arising from the substance or mixture**
Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products**

| Substance | Condition |
|---|---|
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |

Irritant Vapors or Gases During Combustion

**5.3. Special protective actions for fire-fighters**
Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**
Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

**6.2. Environmental precautions**
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**
Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**
For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

**7.2. Conditions for safe storage including any incompatibilities**
Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidizing agents.

# SECTION 8: Exposure controls/personal protection

**8.1. Control parameters**

**Occupational exposure limits**
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---|---|---|---|---|
| Ethylbenzene | 100-41-4 | ACGIH | TWA:20 ppm | A3: Confirmed animal carcin., Ototoxicant |
| Ethylbenzene | 100-41-4 | OSHA | TWA:435 mg/m3(100 ppm) | |
| Toluene | 108-88-3 | ACGIH | TWA:20 ppm | A4: Not class. as human carcin, Ototoxicant |
| Toluene | 108-88-3 | OSHA | TWA:200 ppm;CEIL:300 ppm | |
| Xylene | 1330-20-7 | ACGIH | TWA:20 ppm | A4: Not class. as human carcin |
| Xylene | 1330-20-7 | OSHA | TWA:435 mg/m3(100 ppm) | |

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields
Indirect Vented Goggles

**Skin/hand protection**
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Polymer laminate, Polyvinyl Alcohol (PVA)

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part

of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

| | |
|---|---|
| **Physical state** | Liquid |
| **Color** | Colorless |
| **Odor** | Slight Solvent |
| **Odor threshold** | *No Data Available* |
| **pH** | *Not Applicable* |
| **Melting point/Freezing point** | *Not Applicable* |
| **Boiling point/Initial boiling point/Boiling range** | >=136.1 ºC |
| **Flash Point** | 25 ºC [*Test Method:*Tagliabue Closed Cup] |
| **Evaporation rate** | <=1 [*Ref Std:*BUOAC=1] |
| **Flammability** | Flammable Liquid: Category 3. |
| **Flammable Limits(LEL)** | 1 % |
| **Flammable Limits(UEL)** | 7 % |
| **Vapor Pressure** | <=7.1 mmHg [@ 20 ºC] |
| **Relative Vapor Density** | >=1 [*Ref Std:*AIR=1] |
| **Density** | 0.97 g/ml |
| **Relative Density** | 0.97 [*Test Method:*Tested per ASTM protocol] [*Ref Std:*WATER=1] |
| **Water solubility** | Nil |
| **Solubility- non-water** | *No Data Available* |
| **Partition coefficient: n-octanol/ water** | *No Data Available* |
| **Autoignition temperature** | >=432.2 ºC |
| **Decomposition temperature** | *No Data Available* |
| **Kinematic Viscosity** | 412 mm2/sec |
| **Volatile Organic Compounds** | <=525 g/l |
| **Percent volatile** | 50 - 60 % weight |
| **VOC Less H2O & Exempt Solvents** | <=525 g/l |
| **Molecular weight** | *No Data Available* |

| | |
|---|---|
| **Particle Characteristics** | *Not Applicable* |

## SECTION 10: Stability and reactivity

**10.1. Reactivity**
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**
Stable.

**10.3. Possibility of hazardous reactions**
Hazardous polymerization will not occur.

**10.4. Conditions to avoid**
Heat

Sparks and/or flames

**10.5. Incompatible materials**
Strong oxidizing agents

**10.6. Hazardous decomposition products**

| Substance | Condition |
|---|---|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

**The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.**

**11.1. Information on Toxicological effects**

**Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**
May be harmful if inhaled.
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**
May be harmful in contact with skin.
Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

**Eye Contact:**
Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**
May be harmful if swallowed.
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:**

**Single exposure may cause target organ effects:**
Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Prolonged or repeated exposure may cause target organ effects:**
Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

**Reproductive/Developmental Toxicity:**
Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**
Contains a chemical or chemicals which can cause cancer.

| Ingredient | CAS No. | Class Description | Regulation |
|---|---|---|---|
| Ethylbenzene | 100-41-4 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

**Toxicological Data**
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| Name | Route | Species | Value |
|---|---|---|---|
| Overall product | Dermal | | No data available; calculated ATE >2,000 - =5,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE >20 - =50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >2,000 - =5,000 mg/kg |
| Xylene | Dermal | Rabbit | LD50 > 4,200 mg/kg |
| Xylene | Inhalation-Vapor (4 hours) | Rat | LC50 29 mg/l |
| Xylene | Ingestion | Rat | LD50 3,523 mg/kg |
| Ethylbenzene | Dermal | Rabbit | LD50 15,433 mg/kg |
| Ethylbenzene | Inhalation-Vapor (4 hours) | Rat | LC50 17.4 mg/l |
| Ethylbenzene | Ingestion | Rat | LD50 4,769 mg/kg |
| Toluene | Dermal | Rat | LD50 12,000 mg/kg |
| Toluene | Inhalation-Vapor (4 hours) | Rat | LC50 30 mg/l |
| Toluene | Ingestion | Rat | LD50 5,550 mg/kg |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name | Species | Value |
|---|---|---|
| Xylene | Rabbit | Mild irritant |
| Ethylbenzene | Rabbit | Mild irritant |
| Toluene | Rabbit | Irritant |

**Serious Eye Damage/Irritation**

| Name | Species | Value |
|---|---|---|
| Xylene | Rabbit | Mild irritant |
| Ethylbenzene | Rabbit | Moderate irritant |
| Toluene | Rabbit | Moderate irritant |

**Skin Sensitization**

| Name | Species | Value |
|---|---|---|
| Ethylbenzene | Human | Not classified |
| Toluene | Guinea | Not classified |

| | | |
|---|---|---|
| | pig | |

**Respiratory Sensitization**
For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

| Name | Route | Value |
|---|---|---|
| Xylene | In Vitro | Not mutagenic |
| Xylene | In vivo | Not mutagenic |
| Ethylbenzene | In vivo | Not mutagenic |
| Ethylbenzene | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Toluene | In Vitro | Not mutagenic |
| Toluene | In vivo | Not mutagenic |

**Carcinogenicity**

| Name | Route | Species | Value |
|---|---|---|---|
| Xylene | Dermal | Rat | Not carcinogenic |
| Xylene | Ingestion | Multiple animal species | Not carcinogenic |
| Xylene | Inhalation | Human | Some positive data exist, but the data are not sufficient for classification |
| Ethylbenzene | Inhalation | Multiple animal species | Carcinogenic |
| Toluene | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Ingestion | Rat | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Inhalation | Mouse | Some positive data exist, but the data are not sufficient for classification |

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---|---|---|---|---|---|
| Xylene | Inhalation | Not classified for female reproduction | Human | NOAEL Not available | occupational exposure |
| Xylene | Ingestion | Not classified for development | Mouse | NOAEL Not available | during organogenesis |
| Xylene | Inhalation | Not classified for development | Multiple animal species | NOAEL Not available | during gestation |
| Ethylbenzene | Inhalation | Not classified for development | Rat | NOAEL 4.3 mg/l | premating & during gestation |
| Toluene | Inhalation | Not classified for female reproduction | Human | NOAEL Not available | occupational exposure |
| Toluene | Inhalation | Not classified for male reproduction | Rat | NOAEL 2.3 mg/l | 1 generation |
| Toluene | Ingestion | Toxic to development | Rat | LOAEL 520 mg/kg/day | during gestation |
| Toluene | Inhalation | Toxic to development | Human | NOAEL Not available | poisoning and/or abuse |

**Lactation**

| Name | Route | Species | Value |
|---|---|---|---|
| Xylene | Ingestion | Mouse | Not classified for effects on or via lactation |

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|---|---|---|---|---|---|
| Xylene | Inhalation | auditory system | Causes damage to organs | Rat | LOAEL 6.3 mg/l | 8 hours |
| Xylene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Xylene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Xylene | Inhalation | eyes | Not classified | Rat | NOAEL 3.5 mg/l | not available |
| Xylene | Inhalation | liver | Not classified | Multiple animal species | NOAEL Not available | |
| Xylene | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Multiple animal species | NOAEL Not available | |
| Xylene | Ingestion | eyes | Not classified | Rat | NOAEL 250 mg/kg | not applicable |
| Ethylbenzene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Ethylbenzene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human and animal | NOAEL Not available | |
| Toluene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Toluene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Toluene | Inhalation | immune system | Not classified | Mouse | NOAEL 0.004 mg/l | 3 hours |
| Toluene | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |

### Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|---|---|---|---|---|---|
| Xylene | Inhalation | nervous system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.4 mg/l | 4 weeks |
| Xylene | Inhalation | auditory system | May cause damage to organs though prolonged or repeated exposure | Rat | LOAEL 7.8 mg/l | 5 days |
| Xylene | Inhalation | liver | Not classified | Multiple animal species | NOAEL Not available | |
| Xylene | Inhalation | heart | Not classified | Multiple animal species | NOAEL 3.5 mg/l | 13 weeks |
| Xylene | Inhalation | endocrine system | Not classified | Multiple animal species | NOAEL 3.5 mg/l | 13 weeks |
| Xylene | Inhalation | gastrointestinal tract | Not classified | Multiple animal species | NOAEL 3.5 mg/l | 13 weeks |
| Xylene | Inhalation | hematopoietic system | Not classified | Multiple animal species | NOAEL 3.5 mg/l | 13 weeks |
| Xylene | Inhalation | muscles | Not classified | Multiple animal species | NOAEL 3.5 mg/l | 13 weeks |
| Xylene | Inhalation | kidney and/or bladder | Not classified | Multiple animal | NOAEL 3.5 mg/l | 13 weeks |

| | | | | | | |
|---|---|---|---|---|---|---|
| | | | | species | | |
| Xylene | Inhalation | respiratory system | Not classified | Multiple animal species | NOAEL 3.5 mg/l | 13 weeks |
| Xylene | Ingestion | auditory system | Not classified | Rat | NOAEL 900 mg/kg/day | 2 weeks |
| Xylene | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 1,500 mg/kg/day | 90 days |
| Xylene | Ingestion | liver | Not classified | Multiple animal species | NOAEL Not available | |
| Xylene | Ingestion | heart | Not classified | Mouse | NOAEL 1,000 mg/kg/day | 103 weeks |
| Xylene | Ingestion | skin | Not classified | Mouse | NOAEL 1,000 mg/kg/day | 103 weeks |
| Xylene | Ingestion | endocrine system | Not classified | Mouse | NOAEL 1,000 mg/kg/day | 103 weeks |
| Xylene | Ingestion | bone, teeth, nails, and/or hair | Not classified | Mouse | NOAEL 1,000 mg/kg/day | 103 weeks |
| Xylene | Ingestion | hematopoietic system | Not classified | Mouse | NOAEL 1,000 mg/kg/day | 103 weeks |
| Xylene | Ingestion | immune system | Not classified | Mouse | NOAEL 1,000 mg/kg/day | 103 weeks |
| Xylene | Ingestion | nervous system | Not classified | Mouse | NOAEL 1,000 mg/kg/day | 103 weeks |
| Xylene | Ingestion | respiratory system | Not classified | Mouse | NOAEL 1,000 mg/kg/day | 103 weeks |
| Ethylbenzene | Inhalation | auditory system | May cause damage to organs though prolonged or repeated exposure | Rat | LOAEL 0.9 mg/l | 13 weeks |
| Ethylbenzene | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1.1 mg/l | 2 years |
| Ethylbenzene | Inhalation | liver | Some positive data exist, but the data are not sufficient for classification | Mouse | NOAEL 1.1 mg/l | 103 weeks |
| Ethylbenzene | Inhalation | hematopoietic system | Not classified | Rat | NOAEL 3.4 mg/l | 28 days |
| Ethylbenzene | Inhalation | endocrine system | Not classified | Mouse | NOAEL 3.3 mg/l | 103 weeks |
| Ethylbenzene | Inhalation | gastrointestinal tract | Not classified | Rat | NOAEL 3.3 mg/l | 2 years |
| Ethylbenzene | Inhalation | bone, teeth, nails, and/or hair | Not classified | Multiple animal species | NOAEL 4.2 mg/l | 90 days |
| Ethylbenzene | Inhalation | muscles | Not classified | Multiple animal species | NOAEL 4.2 mg/l | 90 days |
| Ethylbenzene | Inhalation | heart | Not classified | Multiple animal species | NOAEL 3.3 mg/l | 2 years |
| Ethylbenzene | Inhalation | immune system | Not classified | Multiple animal species | NOAEL 3.3 mg/l | 2 years |
| Ethylbenzene | Inhalation | respiratory system | Not classified | Multiple animal species | NOAEL 3.3 mg/l | 2 years |
| Ethylbenzene | Ingestion | liver | Not classified | Rat | NOAEL 680 | 6 months |

| | | | | | | |
|---|---|---|---|---|---|---|
| | | | | | mg/kg/day | |
| Ethylbenzene | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 680 mg/kg/day | 6 months |
| Toluene | Inhalation | auditory system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| Toluene | Inhalation | nervous system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| Toluene | Inhalation | eyes | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| Toluene | Inhalation | olfactory system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| Toluene | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 2.3 mg/l | 15 months |
| Toluene | Inhalation | heart | Not classified | Rat | NOAEL 11.3 mg/l | 15 weeks |
| Toluene | Inhalation | liver | Not classified | Rat | NOAEL 11.3 mg/l | 15 weeks |
| Toluene | Inhalation | kidney and/or bladder | Not classified | Rat | NOAEL 11.3 mg/l | 15 weeks |
| Toluene | Inhalation | endocrine system | Not classified | Rat | NOAEL 1.1 mg/l | 4 weeks |
| Toluene | Inhalation | immune system | Not classified | Mouse | NOAEL Not available | 20 days |
| Toluene | Inhalation | bone, teeth, nails, and/or hair | Not classified | Mouse | NOAEL 1.1 mg/l | 8 weeks |
| Toluene | Inhalation | hematopoietic system | Not classified | Human | NOAEL Not available | occupational exposure |
| Toluene | Inhalation | vascular system | Not classified | Human | NOAEL Not available | occupational exposure |
| Toluene | Inhalation | gastrointestinal tract | Not classified | Multiple animal species | NOAEL 11.3 mg/l | 15 weeks |
| Toluene | Ingestion | nervous system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 625 mg/kg/day | 13 weeks |
| Toluene | Ingestion | heart | Not classified | Rat | NOAEL 2,500 mg/kg/day | 13 weeks |
| Toluene | Ingestion | liver | Not classified | Multiple animal species | NOAEL 2,500 mg/kg/day | 13 weeks |
| Toluene | Ingestion | kidney and/or bladder | Not classified | Multiple animal species | NOAEL 2,500 mg/kg/day | 13 weeks |
| Toluene | Ingestion | hematopoietic system | Not classified | Mouse | NOAEL 600 mg/kg/day | 14 days |
| Toluene | Ingestion | endocrine system | Not classified | Mouse | NOAEL 105 mg/kg/day | 28 days |
| Toluene | Ingestion | immune system | Not classified | Mouse | NOAEL 105 mg/kg/day | 4 weeks |

**Aspiration Hazard**

| Name | Value |
|---|---|
| Xylene | Aspiration hazard |
| Ethylbenzene | Aspiration hazard |
| Toluene | Aspiration hazard |

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

# SECTION 12: Ecological information

## Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

**13.1. Disposal methods**
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable), D018 (Benzene)

## SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

**EPCRA 311/312 Hazard Classifications:**

| **Physical Hazards** |
|---|
| Flammable (gases, aerosols, liquids, or solids) |

| **Health Hazards** |
|---|
| Carcinogenicity |
| Reproductive toxicity |
| Serious eye damage or eye irritation |
| Specific target organ toxicity (single or repeated exposure) |

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

| Ingredient | C.A.S. No | % by Wt |
|---|---|---|
| Xylene | 1330-20-7 | Trade Secret 30 - 60 |
| Ethylbenzene | 100-41-4 | Trade Secret 7 - 13 |

### 15.2. State Regulations
Contact 3M for more information.

### 15.3. Chemical Inventories
The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

**NFPA Hazard Classification**
**Health:** 1 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|---|---|---|---|
| **Document Group:** | 10-0286-4 | **Version Number:** | 36.02 |
| **Issue Date:** | 01/26/26 | **Supersedes Date:** | 09/29/25 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at www.3M.com**