

**ELAN-Plus™ BS-217 Diluent**

Version 6

Revision Date 11/24/2015

Print Date 11/24/2015

**SECTION 1. IDENTIFICATION**

Product name : ELAN-Plus™ BS-217 Diluent

**Manufacturer or supplier's details**

Company : ELANTAS PDG, INC.  
5200 North 2nd Street  
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : [www.elantas.com](http://www.elantas.com)

E-mail address : [Todd.Thomas@altana.com](mailto:Todd.Thomas@altana.com)

Emergency telephone number : INFOTRAC - 1-800-535-5053

**Recommended use of the chemical and restrictions on use**

Recommended use : Resin Reducer

Restrictions on use : Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Aspiration hazard : Category 1

**GHS Label element**

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.

**ELAN-Plus™ BS-217 Diluent**

Version 6

Revision Date 11/24/2015

Print Date 11/24/2015

Precautionary statements : **Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/  
equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ eye protection/ face protection.

**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON  
CENTER or doctor/ physician.  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off  
immediately all contaminated clothing. Rinse skin with water/  
shower.  
P304 + P340 + P312 IF INHALED: Remove victim to fresh air  
and keep at rest in a position comfortable for breathing. Call a  
POISON CENTER or doctor/ physician if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water  
for several minutes. Remove contact lenses, if present and easy  
to do. Continue rinsing.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical advice/  
attention.  
P337 + P313 If eye irritation persists: Get medical advice/  
attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or  
alcohol-resistant foam for extinction.

**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container  
tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**  
P501 Dispose of contents/ container to an approved waste  
disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Vinyl Monomer

**Hazardous components**

**ELAN-Plus™ BS-217 Diluent**

Version 6

Revision Date 11/24/2015

Print Date 11/24/2015

Component	CAS-No.	Concentration (%)
Vinyl toluene	25013-15-4	>= 99 - <= 100

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
 Show this safety data sheet to the doctor in attendance.  
 Symptoms of poisoning may appear several hours later.  
 Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
 If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
 If on skin, rinse well with water.  
 If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
 Remove contact lenses.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
 Do NOT induce vomiting.  
 Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.  
 Take victim immediately to hospital.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.  
 High temperature exposure for extended periods of time will result in spontaneous uncontrolled exothermic polymerization.  
 This increases pressure inside a closed container and may

**ELAN-Plus™ BS-217 Diluent**

Version 6

Revision Date 11/24/2015

Print Date 11/24/2015

- result in the violent rupture of the container.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.

**ELAN-Plus™ BS-217 Diluent**

Version 6

Revision Date 11/24/2015

Print Date 11/24/2015

No smoking.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.  
 High temperature exposure during storage for extended periods of time may result in spontaneous uncontrolled exothermic polymerization. This increases pressure inside a closed container and may result in the violent rupture of the container.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Vinyl toluene	25013-15-4	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		TWA	100 ppm 480 mg/m <sup>3</sup>	OSHA Z-1

**Engineering measures** : Use with adequate ventilation.  
 All application areas should be ventilated in accordance with applicable OSHA regulations. (29 CFR 1910.94)

**Personal protective equipment**

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection  
 Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
 Tightly fitting safety goggles  
 Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.  
 When using do not smoke.

**ELAN-Plus™ BS-217 Diluent**

Version 6

Revision Date 11/24/2015

Print Date 11/24/2015

Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: liquid
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: 127 °F (53 °C) Method: No information available. Information taken from reference works and the literature.
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.896 g/cm <sup>3</sup> (77 °F (25 °C))
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available

**ELAN-Plus™ BS-217 Diluent**

Version 6

Revision Date 11/24/2015

Print Date 11/24/2015

## Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 21 mm<sup>2</sup>/s (104 °F (40 °C))**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Hazardous decomposition products : Carbon monoxide in a fire.  
Hydrocarbons**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation

Skin contact

Eyes

**Acute toxicity****Product:**Acute oral toxicity : Acute toxicity estimate : 2,273 mg/kg  
Method: Calculation methodAcute inhalation toxicity : Acute toxicity estimate : 11.09 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation methodAcute dermal toxicity : Acute toxicity estimate : 4,435 mg/kg  
Method: Calculation method**Components:****25013-15-4 Vinyl toluene:**

Acute oral toxicity : LD50 (Rat): 2,255 mg/kg

Acute dermal toxicity : LD50 (Rabbit): Greater than 4,400 mg/kg

**ELAN-Plus™ BS-217 Diluent**

Version 6

Revision Date 11/24/2015

Print Date 11/24/2015

**Skin corrosion/irritation****Product:**

Remarks: May cause skin irritation in susceptible persons.

**Components:****25013-15-4 Vinyl toluene:**

Species: Rabbit

Result: Moderate skin irritation

**Serious eye damage/eye irritation****Product:**

Remarks: May cause irreversible eye damage.

**Components:****25013-15-4 Vinyl toluene:**

Species: Rabbit

Result: Mild eye irritation

**Respiratory or skin sensitisation****Carcinogenicity****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**ACGIH**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

**ELAN-Plus™ BS-217 Diluent**

Version 6

Revision Date 11/24/2015

Print Date 11/24/2015

by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Aspiration toxicity****Product:**

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks: Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****25013-15-4 Vinyl toluene:**

Toxicity to fish : NOEC (guppy): 1,000 mg/l  
Exposure time: 96 h  
Test Type: static test

Toxicity to daphnia and other : EC0 (Daphnia magna (Water flea)): 1 mg/l  
aquatic invertebrates : Exposure time: 24 h  
Test Type: static test

EC100 (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 24 h  
Test Type: static test

EC100 (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 48 h  
Test Type: static test

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**ELAN-Plus™ BS-217 Diluent**

Version 6

Revision Date 11/24/2015

Print Date 11/24/2015

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

**SECTION 13. DISPOSAL CONSIDERATIONS**
**Disposal methods**

EPA Hazardous Waste Code(s) : D001: Ignitable

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**
**International Regulation****IATA-DGR**

UN/ID No. : UN 2618  
 Proper shipping name : Vinyltoluenes, stabilized  
 Class : 3  
 Packing group : III  
 Labels : Flammable liquid  
 Packing instruction (cargo aircraft) : 366  
 Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 2618  
 Proper shipping name : VINYLTOLUENE, STABILIZED  
 Class : 3  
 Packing group : III  
 Labels : 3

**ELAN-Plus™ BS-217 Diluent**

Version 6

Revision Date 11/24/2015

Print Date 11/24/2015

EmS Code : F-E, S-D  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

UN/ID/NA number : UN 2618  
Proper shipping name : Vinyltoluenes, stabilized  
Class : 3  
Packing group : III  
Labels : Flammable liquid  
Marine pollutant : no

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

**SARA 304 - Emergency Release Notification**

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Acute Health Hazard  
Reactivity Hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

**ELAN-Plus™ BS-217 Diluent**

Version 6

Revision Date 11/24/2015

Print Date 11/24/2015

Vinyl toluene

25013-15-4

99.2 %

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

**Massachusetts Right To Know**

Vinyl toluene

25013-15-4

**Pennsylvania Right To Know**

Vinyl toluene

25013-15-4

**New Jersey Right To Know**

Vinyl toluene

25013-15-4

**New Jersey Trade Secret Registry Number for the product (NJ TSRN)** : NOT APPLICABLE

**California Prop 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

TSCA : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

Section 4 / 12(b) : Not applicable

Section 5 : Not applicable


DSL : We certify that all of the components of this product are listed on the DSL.

**ELAN-Plus™ BS-217 Diluent**

Version 6

Revision Date 11/24/2015

Print Date 11/24/2015

**SECTION 16. OTHER INFORMATION**
**Further information**
**NFPA:**

**HMIS III:**

<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>2</b>
<b>PHYSICAL HAZARD</b>	<b>1</b>

0 = not significant, 1 =Slight,  
 2 = Moderate, 3 = High  
 4 = Extreme, \* = Chronic

Revision Date : 11/24/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.