



Kit Revision Date: 21/08/2024

8332 FAST SET EPOXY

MG Chemicals Multipart Product Kit

This product is a kit made up of multiple parts. Each part is an independently packaged chemical component and has independent hazard assessments.

Kit Content

<i>Part</i>	<i>Product Name</i>	<i>Product Use</i>
A	8332-A	Fast setting epoxy adhesive resin
B	8332-B	Fast setting epoxy adhesive hardener

Safety Data Sheets for each part listed above follow this cover sheet.

Transportation Instruction

Before offering this product kit for transport, read Section 14 for all parts listed above.

8332-A

(PART A)

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 8332-A**Other Means of Identification:** Fast Set Epoxy (Part A)**Related Part #** 8332-25ML, 8332-50ML

Recommended Use and Restriction on Use

Use: Fast setting epoxy adhesive resin**Uses Advised Against:** Not available

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADAMG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

TEL +1-800-340-0772
FAX +1-800-340-0773
E-MAIL support@mgchemicals.com
WEB www.mgchemicals.com

TEL +1-905-331-1396
FAX +1-905-331-2682
E-MAIL info@mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

8332-A**(PART A)****Section 2: Hazard(s) Identification****Classification of the Chemical Chemical****GHS Categories**

Criteria		Category	Signal Word	Pictograms
Sensitization	Skin	1	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Skin Irritation		2	Warning	Exclamation
Hazardous to the Aquatic Environment	Chronic	2	Warning	Environment

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	WARNING
Pictograms	Hazard Statements
	H319: Causes serious eye irritation H315: Cause skin irritation H317: May cause an allergic skin reaction
	H411: Toxic to aquatic life with long lasting effects
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P261	Avoid breathing fumes, mist, and vapors.
P280	Wear protective gloves and eye protection.
P272	Contaminated work clothing should not be allowed out of the workplace.

Section continued on the next page

8332-A
(PART A)
Continued...

Prevention	Precautionary Statements
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
Response	Precautionary Statements
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
25068-38-6	bisphenol-A epoxy resin (reaction product) ^{a)}	≤100%

a) Average molecular weight of ≤700

8332-A

(PART A)

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>redness, irritation, pain</i>
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
IF ON SKIN	P302 + P352, P362 + P364, P333 + P313
Immediate Symptoms	<i>redness, irritation, rash</i>
Response	Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice or attention.
IF INHALED	P304 + P340
Immediate Symptoms	<i>cough, irritation of the respiratory track</i>
Response	Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED	P301 + P330 + P331
Immediate Symptoms	<i>irritation</i>
Response	Rinse mouth. Do not induce vomiting.

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use extinguishing media suitable for surrounding materials.
Specific Hazards	Not flammable or combustible, but will burn if involved in a fire. Produces irritating smoke of unknown toxicity in fires.
Combustion Products	Produces carbon oxides (CO, CO ₂)
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

8332-A

(PART A)

Section 6: Accidental Release Measures

Personal Protection	Use personal protection recommended in Section 8.
Precautions for Response	Avoid breathing the fumes, mist, and vapors.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways. Do not flush to sewer.
Containment Methods	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect the liquid in a sealable, chemical-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wipe off residues with paper towels and place the used towels in the waste container. Wash the spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention	Keep out of reach of children. Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash it before reuse. Avoid breathing fumes, mist, and vapors. Avoid release to the environment.
Handling	Wear protective gloves and eye protection. Wash hands thoroughly after handling. Collect spillage.
Storage	RECOMMENDATION: Keep in a dry and clean area, away from incompatible substances.

8332-A

(PART A)

Section 8: Exposure Controls/Personal Protection**Substances with Occupational Exposure Limit Values**

Contains no substances with occupational exposure limits.

Note: The ACGIH¹, OSHA, and Canadian provinces exposure limits were consulted. Limits from by RTECS database² and data from suppliers' SDS were also consulted.

Engineering Controls**Ventilation**

General ventilation is adequate for normal use; keep overall exposure as low as possible.

Personal Protective Equipment**Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Use safety glasses with lateral protection (side shields).

Skin Protection

For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Respiratory Protection

Generally, for emergencies and exposure above 0.5 mg/m³, use a self-contained breathing apparatus with full face piece operated in a pressure positive mode.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

8332-A

(PART A)

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Clear, yellow tint	Upper Flammability Limit	Not available
Odor	Mild	Vapor Pressure @25 °C^{a)}	$<5.0 \times 10^{-10}$ hPa [$<3.5 \times 10^{-10}$ mmHg]
Odor Threshold	Not available	Vapor Density	Not available
pH	Not available	Relative Density @20 °C	1.16
Freezing/Melting Point	Not available	Solubility in Water	Practically insoluble
Initial Boiling Point	>150 °C [>302 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point	250 °C [482 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Non Flammable	Viscosity @25 °C	$>10\,000$ mm ² /s

a) Literature value for similar composition mixture

Section 10: Stability and Reactivity

Reactivity	Not available.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Avoid flames, excessive temperatures, and incompatible substances.
Incompatibilities	Strong oxidizing agents, strong bases, ammonia
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

8332-A

(PART A)

Section 11: Toxicological Information**Summary of Effects and Symptoms by Routes of Exposure**

Eyes	Causes redness, serious eye irritation, or pain.
Skin	May cause mild to moderate skin irritation.
Inhalation	May cause coughing and irritation of the respiratory tract (nose, throat, and lung).
Ingestion	It may cause irritation.
Chronic	Prolonged and repeated exposure may lead to skin sensitization.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
bisphenol-A epoxy resin (reaction product)	11 400 mg/kg Rat	Not available	Not available

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDSs were also consulted.

Other Toxicological Effects

Skin corrosion/irritation	Causes skin irritant.
Serious eye damage/irritation	Serious to moderate eye irritant
Respiratory and skin sensitization (allergic reactions)	Skin sensitizer based on animal studies on components
Carcinogenicity (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP
Mutagenicity (risk of heritable genetic effects)	Based on available data, classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, classification criteria are not met.

Section continued on the next page

8332-A**(PART A)****STOT-single exposure**

Based on available data, classification criteria are not met.

STOT-repeated exposure

Based on available data, classification criteria are not met.

Aspiration hazard

The liquid content does not meet the aspiration hazard criteria. The mixture doesn't contain category 1 substances.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

In Europe, similar epoxy resin mixtures with CAS# 25068-38-6 and average molecular weight of less than 700 are generally classified as chronic category 2 marine pollutant due to LC50 96 h of >1 mg/L but ≤10 mg/L.

Acute Ecotoxicity

See chronic ecotoxicity.

Chronic Ecotoxicity

Toxic to aquatic life with long lasting effect

Avoid release to the environment. Collect spillage.

Persistence and Biodegradability

Not available

Bioaccumulative Potential

Not available

Mobility in Soil

Not available

Other Effects

Not available

8332-A

(PART A)

Section 13: Disposal Considerations

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information**Ground**

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**

Sizes under 450 L
8332-25ML, 8332-50ML (Part A)
NOT REGULATED in TDG
per Special Provisions 99

Sizes 5 L and under
NOT REGULATED in 49 CFR
per exception 171.4 (c)(2)

49 CFR: Sizes over 5 L
FOR REFERENCE ONLY
UN number: UN3082
Shipping Name: ENVIRONMENTALLY
HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(bisphenol-A epoxy resin (reaction product))
Class: 9
Packing Group: III
Marine Pollutant: Yes

Special Provision 99 (2): These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

171.4 (c) Exceptions:

(2) Single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other requirements of this subchapter provided the packagings meet the general requirements in §§ 173.24 and 173.24a. This exception does not apply to marine pollutants that are a hazardous waste or a hazardous substance. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this subchapter relevant to any additional hazards continue to apply.

Section continued on the next page

8332-A**(PART A)****Air****Refer to ICAO-IATA regulations.**

Sizes 5 L and under
8332-25ML, 8332-50ML (Part A)

NOT REGULATED

On air waybill, write:
"Not Restricted, as per Special
Provisions A197"

Special Provision A197: These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Sea**Refer to IMDG regulations.**

Sizes 5 L and under
8332-25ML, 8332-50ML (Part A)

NOT REGULATED

per 2.10.2.7

2.10.2.7: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

8332-A**(PART A)****Section 15: Regulatory Information****Canada****Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)**


All hazardous ingredients are listed on the DSL/NDSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA**Other Classifications****HMIS® RATING**

HEALTH:	* 2
FLAMMABILITY:	1
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances that are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA)

This product does not contain any listed substances in California.

Section continued on the next page

8332-A**(PART A)****Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

Prepared by the	Regulatory Affairs Department
Date of Revision	07 August 2020
Supersedes	09 March 2020
Reason for Changes:	Added new part number.

Reference

1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
NOELR	No observable effect loading ratio
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Section continued on the next page

8332-A**(PART A)**

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.

8332-B

(PART B)

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 8332-B**Other Means of Identification:** Fast Set Epoxy (Part B)**Related Part #** 8332-25ML, 8332-50ML

Recommended Use and Restriction on Use

Use: fast setting epoxy adhesive hardener**Uses Advised Against:** Not available

Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

MG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

☎ +1-800-340-0772
FAX +1-800-340-0773
E-MAIL support@mgchemicals.com
WEB www.mgchemicals.com

☎ +1-905-331-1396
FAX +1-905-331-2682
E-MAIL info@mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

8332-B
(PART B)
Section 2: Hazard(s) Identification
Classification of the Chemical Material
GHS Categories

Criteria		Category	Signal Word	Pictograms
Skin Corrosion		1	Danger	Corrosion
Eye Corrosion		1	Danger	Corrosion
Sensitization	Skin	1	Warning	Exclamation
Hazardous to the Aquatic Environment	Chronic	3	none	none

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H314: Causes severe skin burns and eye damage
	H317: May cause an allergic skin reaction
No symbol mandated	H412: Harmful to aquatic life with long lasting effects

Section continued on the next page

8332-B
(PART B)
Continued...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P260	Do not breathe fumes, mist, and vapors.
P280	Wear protective gloves and eye protection.
P264	Wash hands and exposed skin thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
Response	Precautionary Statements
P310	For all routes of exposure: Immediately call a POISON CENTER or doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P361 + P352	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P363	Wash contaminated clothing before reuse.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Storage	Precautionary Statements
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, and international regulations.

Hazards Not Otherwise Classified

HCS2012 Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

8332-B
(PART B)
Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
72244-98-5	pentaerythritol-PO-mercaptoglycerol~	84%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	16%

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF IN EYES	P305 + P351 + P338, P310
Immediate Symptoms	<i>redness, pain, burns</i>
Response	Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
IF ON SKIN (or hair)	P303 + P361 + P352, P310, P333 + P313, P363
Immediate Symptoms	<i>redness, allergic contact dermatitis, burns</i>
Response	Take off immediately all contaminated clothing. Wash with plenty of water. Immediately call a POISON CENTER or doctor. If skin irritation or rash occurs: Get medical advice or attention. Wash contaminated clothing before reuse.
IF INHALED	P304 + P340, P310
Immediate Symptoms	<i>cough, irritation of the respiratory track</i>
Response	Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor.
IF SWALLOWED	P301 + P330 + P331, P310
Immediate Symptoms	<i>burns to mouth and throat, abdominal pain (see inhalation symptoms)</i>
Response	Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor.

Section continued on the next page

8332-B**(PART B)****Advice to Physicians**

In case of inhalation of nitrogen oxide combustion products, the symptoms may be delayed. For significant overexposures, the exposed person should be kept under medical surveillance for 48 hours.

Section 5: Fire-Fighting Measures**Extinguishing Media**

In case of fire: Use extinguishing media suitable for surrounding materials.

Specific Hazards

Not flammable or combustible, but will burn if involved in a fire. Produces irritating smoke and toxic smoke in fires.

Inhalation of toxic smoke during fire may have delayed effects. Exposed person may need to be put under surveillance for 48 h.

Harmful to aquatic life: prevent fire fighting wash from entering waterway or sewer system.

Combustion Products

Produces carbon oxides (CO, CO₂), nitrogen oxides (NO_x), sulfur oxides, and hydrogen sulfide.

Fire-Fighter

Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures**Personal Protection**

Use personal protection recommended in Section 8.

Precautions for Response

Do not breathe the vapors, mist, and fumes.

Environmental Precautions

Avoid releasing to the environment. Prevent spill from entering drains and waterways. Do not flush to sewer.

Containment Methods

Contain with inert absorbent (such as soil, sand, vermiculite).

Cleaning Methods

Collect liquid in a sealable, chemical-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wipe the residues with a paper towel and place dirty towels in container. Wash spill area with soap and water to remove the last traces of residue.

Disposal Methods

Dispose spill waste according to Section 13.

8332-B

(PART B)

Section 7: Handling and Storage**Prevention**

Keep out of reach of children.

Do not breathe fumes, mist, and vapors.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Handling

Wear protective gloves and eye protection. Take off contaminated clothing and wash it before reuse.

Wash hands and exposed skin thoroughly after handling.

Storage

Store locked up.

Section 8: Exposure Controls/Personal Protection**Substances with Occupational Exposure Limit Values**

Contains no substances with occupational exposure limits.

Note: The ACGIH¹, OSHA, and Canadian provinces exposure limits were consulted. Limits from the RTECS database² and from suppliers' SDSs were also consulted.

Engineering Controls**Ventilation**

General ventilation is adequate for normal use; keep airborne exposure as low as possible.

Personal Protective Equipment**Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Use safety glasses with lateral protection (side shields).**Skin Protection**

For likely contacts, use butyl rubber, neoprene or other chemically resistant gloves.

For incidental contacts, use disposable nitrile gloves or other chemically resistant gloves.

Section continued on the next page

8332-B
(PART B)

Respiratory Protection If exposed to high levels of fumes, mist, and vapors, wear respirator such as a half-mask respirator with organic vapour cartridges.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Clear yellow	Upper Flammability Limit	Not available
Odor	Mercaptan-like (rotten cabbage)	Vapor Pressure @25 °C	0.000002 hPa estimated
Odor Threshold	Not available	Vapor Density	Not available
pH	Not available	Relative Density @25 °C	1.13
Freezing/Melting Point	Not available	Solubility in Water	Insoluble
Initial Boiling Point	Not available	Partition Coefficient n-octanol/water	Not available
Flash Point	>93.3 °C [>200 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Not applicable	Viscosity @25 °C	$\geq 1\ 000\ \text{mm}^2/\text{s}$

a) Pensky-Martens closed cup

8332-B

(PART B)

Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Avoid excessive heat and incompatible substances. Do not use in a way that forms fumes, vapors, or mist.
Incompatibilities	Strong oxidizing agents, strong acids
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information**Summary of Effects and Symptoms by Routes of Exposure**

Eyes	May cause redness, burns, and pain.
Skin	May cause redness, allergic contact dermatitis, and chemical burns.
Inhalation	Inhalation of fumes, vapors, or mist may cause cough and irritation of the nose, throat, and lungs (upper respiratory tract).
Ingestion	May cause pain and corrosive burns to the mouth, throat, esophagus, and stomach.
Chronic	Prolonged and repeated exposure to uncured epoxy hardener may lead to skin sensitization.

Section continued on the next page

8332-B
(PART B)
Lethal Exposure Concentrations

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
pentaerythritol-PO-mercaptoglycerol~	Not available	Not available	Not available
2,4,6-tris(dimethylaminomethyl) phenol	2 169 mg/kg Rat	>969 mg/kg Rat	Not available

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDSs' were also consulted.

Other Toxicological Effects

Skin corrosion/irritation	Causes severe skin burns.
Serious eye damage/irritation	Causes severe eye damage.
Respiratory and skin sensitization (allergic reactions)	Pentaerythritol-PO-mercaptoglycerol~ and tris-2,4,6-(dimethylaminomethyl) phenol may cause skin sensitization according to animal studies.
Carcinogenicity (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not.
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Based on available data, the classification criteria are not.
Aspiration hazard	Based on available data, the classification criteria are not met. There are no category 1 components, and the kinematic viscosity is >20.5 mm ² /s at 40 °C.

8332-B**(PART B)****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Pentaerythritol-PO-mercaptoglycerol~ and tris-2,4,6-(dimethylaminomethyl) phenol are classified as a chronic aquatic hazard category 3.

Acute Ecotoxicity

See chronic ecotoxicity.

Chronic Ecotoxicity

Category 3

Harmful to aquatic life with long lasting effects

Avoid Release to the environment.

Persistence and Biodegradability

Not available

Bioaccumulative Potential

Not available

Mobility in Soil

Not available

Other Effects

Not available

Section 13: Disposal Considerations

Dispose of contents in accordance with all local, regional, national, and international regulation.


8332-B
(PART B)
Section 14: Transport Information
Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**

Sizes 30 mL and under
8225-25ML, 83321-50ML (Part B)

Excepted Quantity

Code **E2**



** Shipper name


Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 30 mL and under
8225-25ML, 8332-50ML (Part B)

Excepted Quantity

Code **E2**



On air waybill, write:
"Dangerous Goods in
Excepted Quantities".

FOR REFERENCE ONLY

UN number: UN2735

Shipping Name: AMINES, LIQUID
CORROSIVE, N.O.S. (2,4,6-
tris(dimethylaminomethyl)phenol)

Class: 8

Packing Group: II

Marine Pollutant: No


** Shipper name

Section continued on the next page

8332-B
(PART B)
Sea
Refer to IMDG regulations.

Sizes 30 mL and under
8225-25ML, 8332-50ML (Part B)

Excepted Quantity
Code **E2**



In transport document,
write: "Dangerous
Goods in Excepted
Quantities".

FOR REFERENCE ONLY

UN number: UN2735

Shipping Name: AMINES, LIQUID
CORROSIVE, N.O.S. (2,4,6-
tris(dimethylaminomethyl)phenol)

Class: 8

Packing Group: II

Marine Pollutant: No

** Shipper name

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information
Canada
Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.


Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

Section continued on the next page

8332-B**(PART B)****USA****Other Classifications****HMIS[®] RATING**

HEALTH:	* 3
FLAMMABILITY:	1
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA[®] 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances that are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA)

This product does not contain any listed substances in California.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

8332-B

(PART B)

Section 16: Other Information**SDS Prepared by the** Regulatory Affairs Department**Date of Revision** 21 August 2024**Supersedes** 07 August 2020**Reason for Changes:** Update to chemical ingredient name and technical name in section 3 and section 14.**Reference**

1) ACGIH 2023 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
NOELR	No observable effect loading ratio
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Section continued on the next page

8332-B**(PART B)**

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Disclaimer This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.