

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/26/2023

Reviewed on 01/26/2023

### 1 Identification

- **Product identifier**
- **Trade Name:** AC-41
- **Article number:** AC-41
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Von Roll USA, Inc.  
200 Von Roll Drive  
SCHENECTADY, NY 12306  
USA
- **Information department:** Environmental Health and Safety Department
- **Emergency telephone number:**  
During normal opening hours (day-time): +1 (518) 344-7100  
Mahoney 24 hours Emergency Message Service to contact EHS: +1 (518) 793-7788  
For Hazardous Materials [or Dangerous Goods] Incident  
Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC : +1 703-741-5970 / 1-800-424-9300

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 2

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Aspiration Hazard 1

H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

(Contd. on page 2)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/26/2023

Reviewed on 01/26/2023

**Trade Name: AC-41**

(Contd. of page 1)

**· Hazard-determining components of labeling:**

ethylbenzene

toluene

Distillates (petroleum), hydrotreated light

2-butanone oxime

tris(nonylphenyl) phosphite

**· Hazard statements**

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

**· Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Classification system:**

**· NFPA ratings (scale 0 - 4)**



Health = 1  
Fire = 3  
Reactivity = 0

**· HMIS-ratings (scale 0 - 4)**



Health = 1  
Fire = 3  
Reactivity = 0

(Contd. on page 3)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/26/2023

Reviewed on 01/26/2023

**Trade Name: AC-41**

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### \* 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

1330-20-7	xylene	>25-≤50%
100-41-4	ethylbenzene	>2.5-≤10%
96-29-7	2-butanone oxime	≥0.1-≤1%
108-88-3	toluene	≥0.1-≤2.5%
26523-78-4	tris(nonylphenyl) phosphite	≥0.1-≤0.25%
8052-41-3	Stoddard solvent	≥0.1-≤2.5%

### \* 4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

- **Advice for firefighters**

- **Protective equipment:** Mouth respiratory protective device.

### \* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

(Contd. on page 4)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/26/2023

Reviewed on 01/26/2023

**Trade Name: AC-41**

(Contd. of page 3)

*Wear protective equipment. Keep unprotected persons away.*

**Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.

**Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**Protective Action Criteria for Chemicals**

**PAC-1:**

1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
96-29-7	2-butanone oxime	30 ppm
108-88-3	toluene	67 ppm
8052-41-3	Stoddard solvent	300 mg/m <sup>3</sup>
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm

**PAC-2:**

1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
96-29-7	2-butanone oxime	56 ppm
108-88-3	toluene	560 ppm
8052-41-3	Stoddard solvent	1,800 mg/m <sup>3</sup>
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm

**PAC-3:**

1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
96-29-7	2-butanone oxime	250 ppm
108-88-3	toluene	3700* ppm
8052-41-3	Stoddard solvent	29500** mg/m <sup>3</sup>
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm

## 7 Handling and storage

**Handling:**

**Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

**Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

**Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** No special requirements.

(Contd. on page 5)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/26/2023

Reviewed on 01/26/2023

**Trade Name: AC-41**

(Contd. of page 4)

- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

### \* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

<b>1330-20-7 xylene</b>	
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI
<b>100-41-4 ethylbenzene</b>	
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI
<b>96-29-7 2-butanone oxime</b>	
WEEL	Long-term value: 10 ppm DSEN
<b>108-88-3 toluene</b>	
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm BEI, NIC-OTO
<b>8052-41-3 Stoddard solvent</b>	
PEL	Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm
REL	Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min
TLV	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm
<b>· Ingredients with biological limit values:</b>	
<b>1330-20-7 xylene</b>	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

(Contd. on page 6)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 01/26/2023

Reviewed on 01/26/2023

**Trade Name: AC-41**

(Contd. of page 5)

<b>100-41-4 ethylbenzene</b>	
BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	- Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)
<b>108-88-3 toluene</b>	
BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/26/2023

Reviewed on 01/26/2023

**Trade Name: AC-41**

(Contd. of page 6)

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties****· Information on basic physical and chemical properties****· General Information****· Appearance:****Form:** Fluid**Color:** Amber colored**Odor:** Like aromates**Odor threshold:** Not determined.**pH-value:** Not determined.**· Change in condition****Melting point/Melting range:** Undetermined.**Boiling point/Boiling range:** 136 °C (276.8 °F)**Flash point:** 29.4 °C (84.9 °F)**Flammability (solid, gaseous):** Not applicable.**Ignition temperature:** 430 °C (806 °F)**Decomposition temperature:** Not determined.**Auto igniting:** Product is not selfigniting.**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.**· Explosion limits:****Lower:** 1 Vol %**Upper:** 7.8 Vol %**Vapor pressure at 20 °C (68 °F):** 9.5 hPa (7.1 mm Hg)**Density at 20 °C (68 °F):** 0.8987 g/cm³ (7.49965 lbs/gal)**Relative density** Not determined.**Vapor density** Not determined.**Evaporation rate** Not determined.**Solubility in / Miscibility with Water:** Not miscible or difficult to mix.**Partition coefficient (n-octanol/water):** Not determined.**· Viscosity:****Dynamic:** Not determined.**Kinematic:** Not determined.

(Contd. on page 8)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/26/2023

Reviewed on 01/26/2023

**Trade Name: AC-41**

(Contd. of page 7)

**· Solvent content:****Organic solvents:** 55.7 %**VOC content:** 55.7 %

527.0 g/l / 4.40 lb/gal

**· Other information**

No further relevant information available.

\*

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

\*

**11 Toxicological information****· Information on toxicological effects****· Acute toxicity:****· LD/LC50 values that are relevant for classification:****ATE (Acute Toxicity Estimate)**

Dermal	LD50	4,675 mg/kg (rabbit)
Inhalative	LC50/4 h	20.9 mg/l

**1330-20-7 xylene**

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

**100-41-4 ethylbenzene**

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)

**96-29-7 2-butanone oxime**

Oral	LD50	3,700 mg/kg (rat)
Dermal	LD50	200–2,000 mg/kg (rat)
Inhalative	LC50/4 h	20 mg/l (rat)

**108-88-3 toluene**

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

**· Primary irritant effect:****· on the skin:** Irritant to skin and mucous membranes.**· on the eye:** No irritating effect.**· Sensitization:** Sensitization possible through skin contact.**· Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

(Contd. on page 9)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/26/2023

Reviewed on 01/26/2023

**Trade Name: AC-41**

(Contd. of page 8)

*The product can cause inheritable damage.*

**· Carcinogenic categories**

**· IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
108-88-3	toluene	3
136-52-7	cobalt(II) 2-ethylhexanoate	2B

**· NTP (National Toxicology Program)**

*None of the ingredients is listed.*

**· OSHA-Ca (Occupational Safety & Health Administration)**

*None of the ingredients is listed.*

\*

## 12 Ecological information

**· Toxicity**

**Aquatic toxicity:** No further relevant information available.

**Persistence and degradability** No further relevant information available.

**· Behavior in environmental systems:**

**Bioaccumulative potential** No further relevant information available.

**Mobility in soil** No further relevant information available.

**· Additional ecological information:**

**· General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

**· Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**· Other adverse effects** No further relevant information available.

## 13 Disposal considerations

**· Waste treatment methods**

**· Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**· Uncleaned packagings:**

**· Recommendation:** Disposal must be made according to official regulations.

\*

## 14 Transport information

**· UN-Number**

**· DOT, IMDG, IATA**

UN1263

**· UN proper shipping name**

**· DOT, IATA**

Paint

**· IMDG**

PAINT

(Contd. on page 10)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 01/26/2023

Reviewed on 01/26/2023

**Trade Name: AC-41**

(Contd. of page 9)

<b>· Transport hazard class(es)</b>	
<b>· DOT</b>	
	
<b>· Class</b>	3 Flammable liquids
<b>· Label</b>	3
<b>· IMDG, IATA</b>	
	
<b>· Class</b>	3 Flammable liquids
<b>· Label</b>	3
<b>· Packing group</b>	
<b>· DOT, IMDG, IATA</b>	III
<b>· Environmental hazards:</b>	
<b>· Special precautions for user</b>	
<b>· Hazard identification number (Kemler code):</b>	
<b>· EMS Number:</b>	F-E,S-E
<b>· Stowage Category</b>	A
<b>· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	
<b>· Transport/Additional information:</b>	
<b>· DOT</b>	
<b>· Quantity limitations</b>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
<b>· IMDG</b>	
<b>· Limited quantities (LQ)</b>	5L
<b>· Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>· UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

<b>15 Regulatory information</b>
<b>· Safety, health and environmental regulations/legislation specific for the substance or mixture</b>
<b>· Sara</b>
<b>· Section 355 (extremely hazardous substances):</b>
None of the ingredients is listed.
<b>· Section 313 (Specific toxic chemical listings):</b>
1330-20-7 xylene
100-41-4 ethylbenzene

(Contd. on page 11)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 01/26/2023

Reviewed on 01/26/2023

**Trade Name: AC-41**

(Contd. of page 10)

108-88-3	toluene
136-52-7	cobalt(II) 2-ethylhexanoate
112-34-5	2-(2-butoxyethoxy)ethanol

**· TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

**· Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
108-88-3	toluene
136-52-7	cobalt(II) 2-ethylhexanoate

**· Proposition 65**

**· Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**· Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

**· Carcinogenic categories**

**· EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D
108-88-3	toluene	II

**· TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
108-88-3	toluene	A4

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**· GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms**



GHS02



GHS07



GHS08

**· Signal word Danger**

**· Hazard-determining components of labeling:**

ethylbenzene

toluene

Distillates (petroleum), hydrotreated light

2-butanone oxime

tris(nonylphenyl) phosphite

(Contd. on page 12)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/26/2023

Reviewed on 01/26/2023

**Trade Name: AC-41**

(Contd. of page 11)

**· Hazard statements**

- H226 Flammable liquid and vapor.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to the hearing organs through prolonged or repeated exposure.
- H304 May be fatal if swallowed and enters airways.

**· Precautionary statements**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P321 Specific treatment (see on this label).
- P331 Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· National regulations:**

**· Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases** Shelf life: 365 days at room temperature and not recommended at cold room temperature

**· Department issuing SDS:** Environment Health and Safety Department

**· Contact:** Hitesh Surti

**· Date of preparation / last revision** 01/26/2023

**· Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 13)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 01/26/2023

Reviewed on 01/26/2023

**Trade Name: AC-41**

(Contd. of page 12)

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Skin Irritation 2: Skin corrosion/irritation – Category 2

Sensitization - Skin 1: Skin sensitisation – Category 1

Carcinogenicity 2: Carcinogenicity – Category 2

Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1

\* Data compared to the previous version altered.

US