

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/01/2021

Reviewed on 12/01/2021

1 Identification

- **Product identifier**
- **Trade Name:** 3285 Putty Kit
- **Article number:** 3285
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Von Roll USA, Inc.
 200 Von Roll Drive
 SCHENECTADY, NY 12306
 USA
- **Information department:** Environmental Health and Safety Department
- **Emergency telephone number:**
 During normal opening hours (day-time): +1 (518) 344-7100
 Mahoney 24 hours Emergency Message Service to contact EHS: +1 (518) 793-7788
 For Hazardous Materials [or Dangerous Goods] Incident
 Spill, Leak, Fire, Exposure, or Accident
 Call CHEMTREC :+1 703-741-5970 / 1-800-424-9300

2 Hazard(s) identification

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS08 GHS09

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
Diallyl Phthalate
- **Hazard statements**
H370 Causes damage to organs.
H372 Causes damage to organs through prolonged or repeated exposure.
H401 Toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.
P307+P311 IF exposed: Call a POISON CENTER or doctor/physician.
P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment (see on this label).
P391 Collect spillage.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 0
 Fire = 1
 Reactivity = 1

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/01/2021

Reviewed on 12/01/2021

Trade Name: 3285 Putty Kit

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)

HEALTH	*1	Health = *1
FIRE	1	Fire = 1
REACTIVITY	1	Reactivity = 1

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

* 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

546-93-0	Magnesite	>10–≤25%
131-17-9	Diallyl Phthalate	>10–<25%

* 4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/01/2021

Reviewed on 12/01/2021

Trade Name: 3285 Putty Kit

(Contd. of page 2)

- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

546-93-0	Magnesite	45 mg/m ³
131-17-9	Diallyl Phthalate	15 mg/m ³
614-45-9	tert-butyl perbenzoate	8.2 mg/m ³
98-29-3	4-tert-butylcatechol	0.18 mg/m ³

· **PAC-2:**

546-93-0	Magnesite	260 mg/m ³
131-17-9	Diallyl Phthalate	24 mg/m ³
614-45-9	tert-butyl perbenzoate	90 mg/m ³
98-29-3	4-tert-butylcatechol	2 mg/m ³

· **PAC-3:**

546-93-0	Magnesite	1,600 mg/m ³
131-17-9	Diallyl Phthalate	140 mg/m ³
614-45-9	tert-butyl perbenzoate	200 mg/m ³
98-29-3	4-tert-butylcatechol	560 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/01/2021

Reviewed on 12/01/2021

Trade Name: 3285 Putty Kit

(Contd. of page 3)

546-93-0 Magnesite

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV TLV withdrawn

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Store protective clothing separately.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Color: Amber colored

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/01/2021

Reviewed on 12/01/2021

Trade Name: 3285 Putty Kit

(Contd. of page 4)

Boiling point/Boiling range:	Undetermined.
· Flash point:	>93 °C (>199.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 100 °C (212 °F):	0.3 hPa (0.2 mm Hg)
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	4,074 mg/kg (rat)
Dermal	LD50	17,991 mg/kg
Inhalative	LC50/4 h	58.2 mg/l

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/01/2021

Reviewed on 12/01/2021

Trade Name: 3285 Putty Kit

(Contd. of page 5)

131-17-9 Diallyl Phthalate

Oral	LD50	770 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**14807-96-6 Talc (Mg₃H₂(SiO₃)₄)

3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/01/2021

Reviewed on 12/01/2021

Trade Name: 3285 Putty Kit

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA 	UN3082
<ul style="list-style-type: none"> · UN proper shipping name · DOT, IATA · IMDG 	Environmentally hazardous substance, liquid, n.o.s. (Diallyl Phthalate) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diallyl Phthalate), MARINE POLLUTANT
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT, IMDG, IATA <div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label 	9 Miscellaneous dangerous substances and articles 9
<ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA 	III
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: · Special marking (IATA): 	Yes (DOT) Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> · Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	Warning: Miscellaneous dangerous substances and articles 90 F-A,S-F A
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: · DOT · Quantity limitations · Remarks: 	On passenger aircraft/rail: 450 L On cargo aircraft only: 450 L Special marking with the symbol (fish and tree).
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/01/2021

Reviewed on 12/01/2021

Trade Name: 3285 Putty Kit

(Contd. of page 7)

· **UN "Model Regulation":** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIALLYL PHTHALATE), 9, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

14807-96-6 Talc (Mg₃H₂(SiO₃)₄)

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS08 GHS09

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Diallyl Phthalate

· **Hazard statements**

H370 Causes damage to organs.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/01/2021

Reviewed on 12/01/2021

Trade Name: 3285 Putty Kit

(Contd. of page 8)

H372 Causes damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P307+P311 IF exposed: Call a POISON CENTER or doctor/physician.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment (see on this label).

P391 Collect spillage.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases** Shelf life: 180 days at room temperature and 365 days at cold room temperature

· **Department issuing SDS:** Environment Health and Safety Department

· **Contact:** Hitesh Surti

· **Date of preparation / last revision** 12/01/2021 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**