

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2023

Reviewed on 02/03/2023

1 Identification

- **Product identifier**
- **Trade Name:** SYNTHITE®
- **Article number:** ER-41
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Von Roll USA, Inc.
 200 Von Roll Drive
 SCHENECTADY, NY 12306
 USA
- **Information department:** Environmental Health and Safety Department
- **Emergency telephone number:**
 During normal opening hours (day-time): +1 (518) 344-7100
 Mahoney 24 hours Emergency Message Service to contact EHS: +1 (518) 793-7788
 For Hazardous Materials [or Dangerous Goods] Incident
 Spill, Leak, Fire, Exposure, or Accident
 Call CHEMTREC : +1 703-741-5970 / 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226

Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351

Suspected of causing cancer.

Toxic to Reproduction 2

H361

Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 1 H372-H373 Causes damage to organs through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irritation 2

H315

Causes skin irritation.

Sensitization - Skin 1

H317

May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2023

Reviewed on 02/03/2023

Trade Name: SYNTHITE®

(Contd. of page 1)

· **Signal word** *Danger*· **Hazard-determining components of labeling:***ethylbenzene**2-butanone oxime**toluene**cobalt(II) 2-ethylhexanoate**tris(nonylphenyl) phosphite*· **Hazard statements***H226 Flammable liquid and vapor.**H315 Causes skin irritation.**H317 May cause an allergic skin reaction.**H351 Suspected of causing cancer.**H361 Suspected of damaging fertility or the unborn child.**H372-H373 Causes damage to organs through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure.*· **Precautionary statements***P201 Obtain special instructions before use.**P202 Do not handle until all safety precautions have been read and understood.**P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**P233 Keep container tightly closed.**P240 Ground/bond container and receiving equipment.**P241 Use explosion-proof electrical/ventilating/lighting/equipment.**P242 Use only non-sparking tools.**P243 Take precautionary measures against static discharge.**P260 Do not breathe dust/fume/gas/mist/vapors/spray.**P264 Wash thoroughly after handling.**P270 Do not eat, drink or smoke when using this product.**P272 Contaminated work clothing must not be allowed out of the workplace.**P280 Wear protective gloves/protective clothing/eye protection/face protection.**P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**P308+P313 IF exposed or concerned: Get medical advice/attention.**P321 Specific treatment (see on this label).**P314 Get medical advice/attention if you feel unwell.**P362+P364 Take off contaminated clothing and wash it before reuse.**P333+P313 If skin irritation or rash occurs: Get medical advice/attention.**P363 Wash contaminated clothing before reuse.**P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.**P403+P235 Store in a well-ventilated place. Keep cool.**P405 Store locked up.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*· **Classification system:**· **NFPA ratings (scale 0 - 4)***Health = 1**Fire = 3**Reactivity = 0*· **HMIS-ratings (scale 0 - 4)***Health = 1**Fire = 3**Reactivity = 0*

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2023

Reviewed on 02/03/2023

Trade Name: **SYNTHITE®**

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

1330-20-7	xylene	>25–≤50%
100-41-4	ethylbenzene	>2.5–<10%
96-29-7	2-butanone oxime	>2.5–<10%
108-88-3	toluene	≥0.1–≤2.5%
136-52-7	cobalt(II) 2-ethylhexanoate	≥0.1–≤2.5%
26523-78-4	tris(nonylphenyl) phosphite	≥0.1–<0.25%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
Most important symptoms and effects, both acute and delayed No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2023

Reviewed on 02/03/2023

Trade Name: SYNTHITE®

(Contd. of page 3)

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:** *Prevent seepage into sewage system, workpits and cellars.*

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

1330-20-7	xylene	130 ppm
1309-37-1	diiron trioxide	15 mg/m ³
100-41-4	ethylbenzene	33 ppm
108-88-3	toluene	67 ppm

· **PAC-2:**

1330-20-7	xylene	920* ppm
1309-37-1	diiron trioxide	360 mg/m ³
100-41-4	ethylbenzene	1100* ppm
108-88-3	toluene	560 ppm

· **PAC-3:**

1330-20-7	xylene	2500* ppm
1309-37-1	diiron trioxide	2,200 mg/m ³
100-41-4	ethylbenzene	1800* ppm
108-88-3	toluene	3700* ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** *No special requirements.*

· **Information about storage in one common storage facility:** *Not required.*

· **Further information about storage conditions:** *Keep receptacle tightly sealed.*

· **Specific end use(s)** *No further relevant information available.*

US

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2023

Reviewed on 02/03/2023

Trade Name: SYNTHITE®

(Contd. of page 4)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
BEI, A4

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
OTO, BEI, A3

96-29-7 2-butanone oxime

WEEL Long-term value: 10 ppm
DSEN

108-88-3 toluene

PEL Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
BEI, OTO, A4

136-52-7 cobalt(II) 2-ethylhexanoate

TLV Long-term value: 0.02* mg/m³
as Co, A3; *inhalable; DSEN; RSEN; BEI

· **Ingredients with biological limit values:**

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
Medium: urine
Time: end of shift at end of workweek
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2023

Reviewed on 02/03/2023

Trade Name: **SYNTHITE®**

(Contd. of page 5)

108-88-3 toluene

BEI 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2023

Reviewed on 02/03/2023

Trade Name: SYNTHITE®

(Contd. of page 6)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Color:	Red
Odor:	Aromatic
Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

· Flash point: 27 °C (80.6 °F)

· Flammability (solid, gaseous): Flammable.

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapor pressure: Not determined.

· Density: Not determined.

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:

Organic solvents:	44.3 %
VOC content:	50.6 %
	527.3 g/l / 4.40 lb/gal

· Other information: No further relevant information available.

10 Stability and reactivity

· Reactivity: No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions: No dangerous reactions known.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2023

Reviewed on 02/03/2023

Trade Name: SYNTHITE®

(Contd. of page 7)

- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Dermal	LD50	5,621 mg/kg (rabbit)
Inhalative	LC50/4 h	25 mg/l

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
1309-37-1	diron trioxide	3
100-41-4	ethylbenzene	2B
108-88-3	toluene	3
136-52-7	cobalt(II) 2-ethylhexanoate	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2023

Reviewed on 02/03/2023

Trade Name: SYNTHITE®



(Contd. of page 8)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT, IATA** Paint
- **IMDG** PAINT
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **IMDG, IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, IMDG, IATA** III

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2023

Reviewed on 02/03/2023

Trade Name: SYNTHITE®

(Contd. of page 9)

· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E,S-D
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

*

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
100-41-4	ethylbenzene
108-88-3	toluene
136-52-7	cobalt(II) 2-ethylhexanoate

· **TSCA (Toxic Substances Control Act):**

	Oil Modified Polyurethane Resin	ACTIVE
1330-20-7	xylene	ACTIVE
1309-37-1	diiron trioxide	ACTIVE
100-41-4	ethylbenzene	ACTIVE
64742-47-8	Distillates (petroleum), hydrotreated light	ACTIVE
108-88-3	toluene	ACTIVE
22464-99-9	Zirconium	ACTIVE
136-52-7	cobalt(II) 2-ethylhexanoate	ACTIVE
26523-78-4	tris(nonylphenyl) phosphite	ACTIVE
7585-20-8	Zirconium Acetate	ACTIVE

· **Hazardous Air Pollutants**

1330-20-7	xylene
-----------	--------

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2023

Reviewed on 02/03/2023

Trade Name: **SYNTHITE®**

(Contd. of page 10)

100-41-4	ethylbenzene
108-88-3	toluene
136-52-7	cobalt(II) 2-ethylhexanoate

· **Proposition 65**· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D
108-88-3	toluene	II

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
1309-37-1	diiron trioxide	A4
100-41-4	ethylbenzene	A3
108-88-3	toluene	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

ethylbenzene

2-butanone oxime

toluene

cobalt(II) 2-ethylhexanoate

tris(nonylphenyl) phosphite

· **Hazard statements**

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H372-H373 Causes damage to organs through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/08/2023

Reviewed on 02/03/2023

Trade Name: SYNTHITE®

(Contd. of page 11)

· Precautionary statements

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P321 Specific treatment (see on this label).
- P314 Get medical advice/attention if you feel unwell.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases** Shelf life: 365 days at room temperature and not recommended at cold room temperature

· **Department issuing SDS:** Environment Health and Safety Department

· **Contact:** Hitesh Surti

· **Date of preparation / last revision** 02/03/2023

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/08/2023

Reviewed on 02/03/2023

Trade Name: SYNTHITE®

(Contd. of page 12)

*Flammable Liquids 3: Flammable liquids – Category 3**Skin Irritation 2: Skin corrosion/irritation – Category 2**Sensitization - Skin 1: Skin sensitisation – Category 1**Carcinogenicity 2: Carcinogenicity – Category 2**Toxic to Reproduction 2: Reproductive toxicity – Category 2**Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1**. * Data compared to the previous version altered.*

US