



- NOTES:  
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.  
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.  
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

1525	286T	28.12	---	15.37	11.00	9.50	9.50	.92
1375	284T	26.62	---	13.87	9.50	---	---	.92
DASH	FRAME	C	AG	B	2F	2FF	2FFF	BS

		TOLERANCES UNLESS SPECIFIED		Lincoln MOTORS		DRAWN TJB 09-05-2001	
		DEC.	INCHES			CHK	DRS 09-05-2001
4	0.75 CONDUIT WAS 0.75 HOLE CN 38458	HLB	09-28-2004	ML	.X	±.1	APPD JMM 09-05-2001
3	REVISED 2FF DIMENSION CN 33454	TAT	03-26-2004	ML	.XX	±.03	SCALE 1=4
2	KEY WAS .38X.38X1.88 CN 31701	BJK	07-24-2002	ML	.XXX	±.005	REF
1	NEW DRAWING	TJB	09-06-2001	CHK	.XXXX	±.0005	FMV
NO.	REVISION	BY & DATE		CHK	ANG	±7'30"	PREV
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE xf5f1ss1		SIZE DRAWING NO. PAGE OF REV.
				DIST	LB	B	XF5F1SS1 4