

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

1 Identification

· **Product identifier**

· **Trade Name:** 74043

· **Article number:** 74043

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Von Roll USA, Inc.
200 Von Roll Drive
SCHENECTADY, NY 12306
USA

· **Information department:** Environmental Health and Safety Department

· **Emergency telephone number:**

During normal opening hours (day-time): +1 (518) 344-7100
Mahoney 24 hours Emergency Message Service to contact EHS: +1 (518) 793-7788
For Hazardous Materials [or Dangerous Goods] Incident
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC :+1 703-741-5970 / 1-800-424-9300

2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1B H350 May cause cancer.

Repr. 1B H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

Trade Name: 74043

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS05 GHS07 GHS08

· **Signal word** *Danger*· **Hazard-determining components of labeling:**

butan-1-ol
ethylbenzene
1-methoxy-2-propanol
bisphenol A
Formaldehyde

· **Hazard statements**

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H350 May cause cancer.
H360 May damage fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P321 Specific treatment (see on this label).
P314 Get medical advice/attention if you feel unwell.
P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

Trade Name: 74043

(Contd. of page 2)

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

1330-20-7	xylene	>10-≤25%
107-98-2	1-methoxy-2-propanol	>10-<20%
71-36-3	butan-1-ol	≥3-<10%
100-41-4	ethylbenzene	>2.5-<10%
34590-94-8	Dipropylene glycol monomethyl ether	>2.5-≤10%
80-05-7	bisphenol A	≥1-≤2.5%
50-00-0	Formaldehyde	≥0.1-<1%

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

Trade Name: 74043

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

1330-20-7	xylene	130 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
71-36-3	butan-1-ol	60 ppm
100-41-4	ethylbenzene	33 ppm
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
80-05-7	bisphenol A	15 mg/m ³
50-00-0	Formaldehyde	0.90 ppm
67-56-1	methanol	530 ppm

· PAC-2:

1330-20-7	xylene	920* ppm
107-98-2	1-methoxy-2-propanol	160 ppm
71-36-3	butan-1-ol	800 ppm
100-41-4	ethylbenzene	1100* ppm
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
80-05-7	bisphenol A	110 mg/m ³
50-00-0	Formaldehyde	14 ppm
67-56-1	methanol	2,100 ppm

· PAC-3:

1330-20-7	xylene	2500* ppm
-----------	--------	-----------

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

Trade Name: 74043

(Contd. of page 4)

107-98-2	1-methoxy-2-propanol	660 ppm
71-36-3	butan-1-ol	8000** ppm
100-41-4	ethylbenzene	1800* ppm
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
80-05-7	bisphenol A	650 mg/m ³
50-00-0	Formaldehyde	56 ppm
67-56-1	methanol	7200* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm
BEI	

107-98-2 1-methoxy-2-propanol

REL	Short-term value: 540 mg/m ³ , 150 ppm Long-term value: 360 mg/m ³ , 100 ppm
-----	---

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

Trade Name: 74043

(Contd. of page 5)

TLV Short-term value: 369 mg/m³, 100 ppm
Long-term value: 184 mg/m³, 50 ppm

71-36-3 butan-1-ol

PEL Long-term value: 300 mg/m³, 100 ppm
REL Ceiling limit value: 150 mg/m³, 50 ppm
Skin
TLV Long-term value: 61 mg/m³, 20 ppm

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm
REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm
TLV Long-term value: 87 mg/m³, 20 ppm
BEI

34590-94-8 Dipropylene glycol monomethyl ether

PEL Long-term value: 600 mg/m³, 100 ppm
Skin
REL Short-term value: 900 mg/m³, 150 ppm
Long-term value: 600 mg/m³, 100 ppm
Skin
TLV Short-term value: NIC-606 (909) mg/m³, NIC-100 (150) ppm
Long-term value: NIC-303 (606) mg/m³, NIC-50 (100) ppm
(Skin)

50-00-0 Formaldehyde

PEL Short-term value: 2 ppm
Long-term value: 0.75 ppm
see 29 CFR 1910.1048(c)
REL Long-term value: 0.016 ppm
Ceiling limit value: 0.1* ppm
*15-min; See Pocket Guide App. A
TLV Short-term value: 0.37 mg/m³, 0.3 ppm
Long-term value: 0.12 mg/m³, 0.1 ppm
DSEN; RSEN

· Ingredients with biological limit values:**1330-20-7 xylene**

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine
Medium: urine
Time: end of shift at end of workweek
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-
Medium: end-exhaled air
Time: not critical
Parameter: Ethyl benzene (semi-quantitative)

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

Trade Name: 74043

(Contd. of page 6)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Color: Amber colored

· **Odor:** Solvent

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 116–118 °C (240.8–244.4 °F)

· **Flash point:** 15 °C (59 °F)

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

Trade Name: 74043

(Contd. of page 7)

· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	270 °C (518 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	~20 Vol %
· Vapor pressure at 20 °C (68 °F):	12 hPa (9 mm Hg)
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	48.2 %
VOC content:	48.2 %
	491.0 g/l / 4.10 lb/gal
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral	LD50	16,256 mg/kg (rat)

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

Trade Name: 74043

(Contd. of page 8)

Dermal	LD50	9,627 mg/kg (rabbit)
Inhalative	LC50/4 h	45 mg/l
1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
107-98-2 1-methoxy-2-propanol		
Oral	LD50	5,660 mg/kg (rat)
Dermal	LD50	13,000 mg/kg (rabbit)
71-36-3 butan-1-ol		
Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (rat)
100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)
34590-94-8 Dipropylene glycol monomethyl ether		
Oral	LD50	5,135 mg/kg (rat)
Dermal	LD50	>19,000 mg/kg (rab)
80-05-7 bisphenol A		
Oral	LD50	3,250 mg/kg (rat)
Dermal	LD50	3,000 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
50-00-0	Formaldehyde	1

- **NTP (National Toxicology Program)**

50-00-0	Formaldehyde	K
---------	--------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

50-00-0	Formaldehyde	
---------	--------------	--

* 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

Trade Name: 74043

(Contd. of page 9)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
*Water hazard class 3 (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Must not reach bodies of water or drainage ditch undiluted or unneutralized.
 Danger to drinking water if even extremely small quantities leak into the ground.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---------------------|
| · UN-Number | |
| · DOT, IMDG, IATA | UN1866 |
| · UN proper shipping name | |
| · DOT, IATA | Resin solution |
| · IMDG | RESIN SOLUTION |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | |
| · DOT, IMDG, IATA | II |

(Contd. on page 11)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

Trade Name: 74043

(Contd. of page 10)

· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-D
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

50-00-0	Formaldehyde
---------	--------------

· Section 313 (Specific toxic chemical listings):

1330-20-7	xylene
-----------	--------

71-36-3	butan-1-ol
---------	------------

100-41-4	ethylbenzene
----------	--------------

80-05-7	bisphenol A
---------	-------------

50-00-0	Formaldehyde
---------	--------------

67-56-1	methanol
---------	----------

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

1330-20-7	xylene
-----------	--------

100-41-4	ethylbenzene
----------	--------------

50-00-0	Formaldehyde
---------	--------------

67-56-1	methanol
---------	----------

· Proposition 65

· Chemicals known to cause cancer:

100-41-4	ethylbenzene
----------	--------------

50-00-0	Formaldehyde
---------	--------------

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

Trade Name: 74043

(Contd. of page 11)

· **Chemicals known to cause reproductive toxicity for females:**

80-05-7 bisphenol A

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

80-05-7 bisphenol A

67-56-1 methanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

71-36-3 butan-1-ol

D

100-41-4 ethylbenzene

D

50-00-0 Formaldehyde

B1

· **TLV (Threshold Limit Value)**

1330-20-7 xylene

A4

100-41-4 ethylbenzene

A3

50-00-0 Formaldehyde

A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

50-00-0 Formaldehyde

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS05

GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

butan-1-ol

ethylbenzene

1-methoxy-2-propanol

bisphenol A

Formaldehyde

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

Trade Name: 74043

(Contd. of page 12)

- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a poison center/doctor.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P321 Specific treatment (see on this label).
- P314 Get medical advice/attention if you feel unwell.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases** Shelf life: 180 days at room temperature and not recommended at cold room temperature

· **Department issuing SDS:** Environment Health and Safety Department

· **Contact:** Hitesh Surti

· **Date of preparation / last revision** 05/04/2021 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

(Contd. on page 14)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/04/2021

Reviewed on 05/04/2021

Trade Name: 74043

(Contd. of page 13)

*OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flam. Liq. 2: Flammable liquids – Category 2**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Skin Sens. 1: Skin sensitisation – Category 1**Carc. 1B: Carcinogenicity – Category 1B**Repr. 1B: Reproductive toxicity – Category 1B**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2***· * Data compared to the previous version altered.**

US