



SAFETY DATA SHEET

DOW SILICONES CORPORATION

Product name: DOWSIL™ 1-2577 Conformal Coating

Issue Date: 01/03/2022

Print Date: 01/07/2022

DOW SILICONES CORPORATION encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: DOWSIL™ 1-2577 Conformal Coating

Recommended use of the chemical and restrictions on use

Identified uses: Semiconductors

COMPANY IDENTIFICATION

DOW SILICONES CORPORATION
2200 WEST SALZBURG ROAD
MIDLAND MI 48686-0994
UNITED STATES

Customer Information Number:

800-258-2436
SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1 800 424 9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids - Category 2

Skin irritation - Category 2

Skin sensitisation - Category 1

Reproductive toxicity - Category 2

Specific target organ toxicity - single exposure - Category 3

Specific target organ toxicity - repeated exposure - Category 2 - Inhalation

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

Highly flammable liquid and vapour.
Causes skin irritation.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
May cause damage to organs (Nervous system) through prolonged or repeated exposure if inhaled.

Precautionary statements

Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical, ventilating or lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves, protective clothing, eye protection and/or face protection.

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
IF exposed or concerned: Get medical advice/ attention.
If skin irritation or rash occurs: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal

Dispose of contents and/or container to an approved waste disposal plant.

Other hazards

Static-accumulating flammable liquid.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone in solvent

This product is a mixture.

Component	CASRN	Concentration
Toluene	108-88-3	>= 21.0 - <= 24.0 %
Methyltrimethoxysilane	1185-55-3	>= 4.0 - <= 5.0 %
Octamethyl Cyclotetrasiloxane	556-67-2	>= 0.21 - <= 0.45 %

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation or rash occurs. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be available in work area.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. Suitable emergency eye wash facility should be available in work area.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if inhaled.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. Alcohol consumed before or after exposure may increase adverse effects. No specific antidote. Treatment of exposure

should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam. Dry chemical. Dry sand.

Unsuitable extinguishing media: High volume water jet. Do not use direct water stream..

Special hazards arising from the substance or mixture

Hazardous combustion products: Silicon oxides. Formaldehyde. Carbon oxides.

Unusual Fire and Explosion Hazards: Flash back possible over considerable distance.. Exposure to combustion products may be a hazard to health.. Flammable concentrations of vapor can accumulate at temperatures above flash point; see Section 9.. Flammable mixtures may exist within the vapor space of containers at room temperature.. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat.. Vapours may form explosive mixtures with air..

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage.. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.. Do not use a solid water stream as it may scatter and spread fire.. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Ventilate the area. Use personal protective equipment. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Ground and bond all containers and handling equipment. Vapor explosion hazard. Keep out of sewers. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get on skin or clothing. Do not breathe vapours or spray mist. Avoid contact with eyes. Do not swallow. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Non-sparking tools should be used. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation. Ensure all equipment is electrically grounded before beginning transfer operations. This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations. Restrict flow velocity in order to reduce the accumulation of static electricity. Ground and bond container and receiving equipment.

Conditions for safe storage: Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Flammable solids. Pyrophoric liquids. Pyrophoric solids. Self-heating substances and mixtures. Substances and mixtures, which in contact with water, emit flammable gases. Explosives. Gases. Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Toluene	ACGIH	TWA	20 ppm
	Further information: Ototoxicant; A4: Not classifiable as a human carcinogen		
	OSHA Z-2	TWA	200 ppm
	OSHA Z-2	CEIL	300 ppm
Methyltrimethoxysilane	OSHA Z-2	Peak	500 ppm
	Dow IHG	TWA	7.5 ppm
	Further information: Skin Sensitizer		
Octamethyl Cyclotetrasiloxane	US WEEL	TWA	10 ppm
Methanol	ACGIH	TWA	200 ppm

Further information: Skin: Danger of cutaneous absorption			
ACGIH	STEL	250 ppm	
Further information: Skin: Danger of cutaneous absorption			
OSHA Z-1	TWA	260 mg/m3 200 ppm	

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing: Methanol.

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). NOTICE: The selection of a specific glove for a particular application

and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. When respiratory protection is required, use an approved positive-pressure self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	liquid
Color	yellow
Odor	strong
Odor Threshold	No data available
pH	Not applicable, substance/mixture is non-polar/aprotic
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	> 65 °C (> 149 °F)
Flash point	Seta closed cup 5 °C (41 °F)
Evaporation Rate (Butyl Acetate = 1)	No data available
Flammability (solid, gas)	Not applicable
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	1.04
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Kinematic Viscosity	800 cSt at 25 °C (77 °F)
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.

Molecular weight No data available
Particle size Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents. Vapours may form explosive mixture with air. Highly flammable liquid and vapour.

Conditions to avoid: Avoid static discharge. Heat, flames and sparks.

Incompatible materials: Avoid contact with oxidizing materials.

Hazardous decomposition products:

Decomposition products can include and are not limited to: Methanol. Benzene. Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Information on likely routes of exposure

Inhalation, Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute Toxicity Endpoints:

Not classified based on available information.

Acute oral toxicity

Information for the Product:

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

As product: Single dose oral LD50 has not been determined.

Based on product testing:
LD50, Rat, > 2,000 mg/kg

Information for components:

Toluene

LD50, Rat, 5,580 mg/kg

Methyltrimethoxysilane

LD50, Rat, male and female, 11,685 mg/kg

This substance may hydrolyze to release Methanol. Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart.

Octamethyl Cyclotetrasiloxane

LD50, Rat, male, > 4,800 mg/kg No deaths occurred at this concentration.

Acute dermal toxicity

Information for the Product:

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):
LD50, > 2,000 mg/kg Estimated.

Information for components:

Toluene

LD50, Rabbit, 12,267 mg/kg

Methyltrimethoxysilane

LD50, Rabbit, male and female, > 9,500 mg/kg OECD 402 or equivalent

This substance may hydrolyze to release Methanol. Effects of methanol are the same as observed via oral and inhalation exposure and include central nervous system (CNS) depression, visual impairment up to blindness, metabolic acidosis, with effects on organ systems such as liver, kidneys and heart, even death.

Octamethyl Cyclotetrasiloxane

LD50, Rat, male and female, > 2,400 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity

Information for the Product:

Vapor concentrations are attainable which could be hazardous on single exposure. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. Alcohol consumption and exertion may increase the adverse effects of toluene.

As product: The LC50 has not been determined.

Information for components:

Toluene

LC50, Rat, male, 4 Hour, vapour, 25.7 mg/l

LC50, Rat, female, 4 Hour, vapour, 30 mg/l

Methyltrimethoxysilane

LC50, Rat, male and female, 6 Hour, vapour, > 7605 ppm OECD Test Guideline 403

This substance may hydrolyze to release Methanol. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death.

Octamethyl Cyclotetrasiloxane

LC50, Rat, male and female, 4 Hour, dust/mist, 36 mg/l OECD Test Guideline 403

Skin corrosion/irritation

Causes skin irritation.

Information for the Product:

Based on product testing:

Brief contact may cause slight skin irritation with local redness.

Prolonged contact may cause moderate skin irritation with local redness.

May cause drying and flaking of the skin.

Information for components:

Toluene

Brief contact may cause slight skin irritation with local redness.

Prolonged contact may cause moderate skin irritation with local redness.

May cause drying and flaking of the skin.

Methyltrimethoxysilane

Brief contact may cause slight skin irritation with local redness.

Octamethyl Cyclotetrasiloxane

Brief contact is essentially nonirritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Information for the Product:

Based on information for component(s):

May cause slight eye irritation.

May cause slight temporary corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Vapor may cause lacrimation (tears).

Information for components:

Toluene

May cause slight eye irritation.

May cause slight temporary corneal injury.
Vapor may cause eye irritation experienced as mild discomfort and redness.
Vapor may cause lacrimation (tears).

Methyltrimethoxysilane

May cause slight temporary eye irritation.
Corneal injury is unlikely.

Octamethyl Cyclotetrasiloxane

Essentially nonirritating to eyes.

Sensitization

For skin sensitization:

May cause an allergic skin reaction.

For respiratory sensitization:

Not classified based on available information.

Information for the Product:

For skin sensitization:

Contains component(s) which have caused allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

Information for components:

Toluene

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Methyltrimethoxysilane

For skin sensitization:

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Octamethyl Cyclotetrasiloxane

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

May cause drowsiness or dizziness.

Information for the Product:

Product test data not available.

Information for components:

Toluene

May cause drowsiness or dizziness.

Route of Exposure: Inhalation

Target Organs: Central nervous system

Methyltrimethoxysilane

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Octamethyl Cyclotetrasiloxane

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Aspiration Hazard

Not classified based on available information.

Information for the Product:

Based on physical properties, not likely to be an aspiration hazard.

Information for components:

Toluene

May be fatal if swallowed and enters airways.

Methyltrimethoxysilane

Material is not classified as an aspiration hazard based on insufficient data, however materials with low viscosity may be aspirated into the lungs during ingestion or vomiting.

Octamethyl Cyclotetrasiloxane

May be harmful if swallowed and enters airways.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

May cause damage to organs (Nervous system) through prolonged or repeated exposure if inhaled.

Information for the Product:

Product test data not available.

Information for components:

Toluene

In animals, effects have been reported on the following organs:

Central nervous system.

Excessive exposure may cause neurologic signs and symptoms.

Toluene has caused hearing loss in laboratory animals upon exposure to high concentrations.
Intentional misuse by deliberately inhaling toluene may cause nervous system damage, hearing loss, liver and kidney effects and death.

Methyltrimethoxysilane

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Octamethyl Cyclotetrasiloxane

In animals, effects have been reported on the following organs:

- Kidney.
- Liver.
- Respiratory tract.
- Female reproductive organs.

Carcinogenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Toluene

Did not cause cancer in laboratory animals.

Methyltrimethoxysilane

No relevant data found.

Octamethyl Cyclotetrasiloxane

Results from a 2 year repeated vapour inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

Teratogenicity

Suspected of damaging fertility or the unborn child.

Information for the Product:

Product test data not available.

Information for components:

Toluene

In laboratory animals, toluene has been toxic to the fetus at doses toxic to the mother; it has caused birth defects in mice when administered orally, but not by inhalation.

Methyltrimethoxysilane

Did not cause birth defects or any other fetal effects in laboratory animals.

Octamethyl Cyclotetrasiloxane

Did not cause birth defects or any other fetal effects in laboratory animals.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Information for the Product:

Product test data not available.

Information for components:

Toluene

In animal studies, did not interfere with reproduction.

Methyltrimethoxysilane

In animal studies, did not interfere with reproduction.

Octamethyl Cyclotetrasiloxane

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. In animal studies, has been shown to interfere with fertility.

Mutagenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Toluene

The majority and most reliable of the many genetic toxicity studies on toluene, both in vitro and in animals, indicate that it is not genetically toxic.

Methyltrimethoxysilane

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

Octamethyl Cyclotetrasiloxane

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Toluene

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 5.8 mg/l

Acute toxicity to aquatic invertebrates

LC50, water flea Ceriodaphnia dubia, semi-static test, 48 Hour, 3.78 mg/l

Acute toxicity to algae/aquatic plants

EbC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Biomass, 12.5 mg/l, OECD Test Guideline 201

Toxicity to bacteria

IC50, Bacteria, 16 Hour, 29 mg/l

Chronic toxicity to fish

NOEC, Fish, flow-through test, 40 d, growth, 1.4 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Ceriodaphnia dubia (water flea), 7 d, number of offspring, 0.74 mg/l

Toxicity to soil-dwelling organisms

LC50, Eisenia fetida (earthworms), 150 - 280 mg/kg

Methyltrimethoxysilane

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 110 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), flow-through test, 48 Hour, > 122 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

No toxicity at the limit of solubility

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, > 3.6 mg/l, OECD Test Guideline 201

No toxicity at the limit of solubility

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, >= 3.6 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC10, activated sludge, 3 Hour, Respiration rates., > 100 mg/l, OECD Test Guideline 209

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 28 d, number of offspring, >= 10 mg/l

Octamethyl Cyclotetrasiloxane

Acute toxicity to fish

Based on testing of comparable products: The estimated maximum aqueous concentration of Octamethyl Cyclotetrasiloxane (D4) from migration to water from the product as supplied is below the D4 established no-effect threshold (< 0.0079 mg/L) for aquatic organisms.

Chronic toxicity to aquatic invertebrates

Based on testing for product(s) in this family of materials:
Not classified due to data which are conclusive although insufficient for classification.

Persistence and degradability**Toluene**

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Not applicable

Biodegradation: 100 %

Exposure time: 14 d

Method: OECD Test Guideline 301C or Equivalent

Theoretical Oxygen Demand: 3.13 mg/mg Calculated.

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 2 d

Method: Estimated.

Methyltrimethoxysilane

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

Biodegradation: 54 %

Exposure time: 28 d

Method: Regulation (EC) No. 440/2008, Annex, C.4-A

Octamethyl Cyclotetrasiloxane

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Not applicable

Biodegradation: 3.7 %

Exposure time: 28 d

Method: OECD Test Guideline 310

Stability in Water (1/2-life)

Hydrolysis, DT50, 3.9 d, pH 7, Half-life Temperature 25 °C, OECD Test Guideline 111

Bioaccumulative potential**Toluene**

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 2.73 Measured

Bioconcentration factor (BCF): 13.2 - 90 Fish Measured

Methyltrimethoxysilane**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).**Partition coefficient: n-octanol/water(log Pow):** -0.82 Estimated.**Octamethyl Cyclotetrasiloxane****Bioaccumulation:** Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).**Partition coefficient: n-octanol/water(log Pow):** 6.49 Measured**Bioconcentration factor (BCF):** 12,400 Pimephales promelas (fathead minnow) Measured**Mobility in soil****Toluene****Partition coefficient (Koc):** 37 - 178 Estimated.**Methyltrimethoxysilane**

No relevant data found.

Octamethyl Cyclotetrasiloxane**Partition coefficient (Koc):** 16596 OECD Test Guideline 106

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Flammable liquids, n.o.s.(Toluene, Methyltrimethoxysilane)
UN number	UN 1993
Class	3
Packing group	II
Reportable Quantity	Toluene

Classification for SEA transport (IMO-IMDG):

Proper shipping name	FLAMMABLE LIQUID, N.O.S.(Toluene, Methyltrimethoxysilane)
UN number	UN 1993
Class	3
Packing group	II
Marine pollutant	No
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Flammable liquid, n.o.s.(Toluene, Methyltrimethoxysilane)
UN number	UN 1993
Class	3
Packing group	II

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Flammable (gases, aerosols, liquids, or solids)
 Hazard not otherwise classified (physical hazards)
 Respiratory or skin sensitisation
 Reproductive toxicity
 Specific target organ toxicity (single or repeated exposure)
 Skin corrosion or irritation

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

The following components are subject to reporting levels established by SARA Title III, Section 313:

Components	CASRN
Toluene	108-88-3

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
-------------------	--------------

Dimethyl, methylmethoxy, phenylmethoxy siloxane with methyl and phenyl silsesquioxanes	68952-93-2
Toluene	108-88-3
Methyltrimethoxysilane	1185-55-3

California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, Benzene, Distillates (petroleum), hydrotreated middle, Cumene, which is/are known to the State of California to cause cancer, and Toluene, Methanol, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System**NFPA**

Health	Flammability	Instability
2	3	0

HMIS

Health	Flammability	Physical Hazard
2*	3	0

* = Chronic Effects (See Hazards Identification)

Revision

Identification Number: 1689231 / A713 / Issue Date: 01/03/2022 / Version: 12.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
CEIL	Acceptable ceiling concentration
Dow IHG	Dow Industrial Hygiene Guideline
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	USA. Occupational Exposure Limits (OSHA) - Table Z-2
Peak	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
STEL	Short-term exposure limit
TWA	Time weighted average
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the

German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW SILICONES CORPORATION urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US