



Set Revision Date: 11 February 2025

## **ELECTROSOLVE™ CONTACT CLEANER**

### **MG Chemicals Product with Chemical Variance**

This document contains safety data sheets related to the same product name. However, different sizes use different propellants with equivalent toxicity. Please refer to the list below to determine which safety data sheet relates to your purchased product.

#### **Kit Content**

<i>Part #</i>	<i>Propellant</i>
409B-140G	1,1,1,2-tetrafluoroethane (HFC-134a)
409B-340G	1,1-difluoroethane (HFC-152a)

*Safety Data Sheets for each part listed above follow this cover sheet.*

409B-140G

(AEROSOL)

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Identifier:** 409B-140G**Other Means Of Identification:** Electrosolve™ Contact Cleaner**Related Part #** 409B-140G

### Recommended Use and Restriction on Use

**Use:** Zero-residue contact cleaner**Uses Advised Against:** Do not use on live circuits or in presence of ignition source

### Details of Manufacturer or Importer

**Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADA**Distributor**Mouser Electronic  
1000 North Main Street  
Mansfield, TX 76063  
USA

☎ +1-905-331-1396

+1 800-340-0772

**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number

**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**

(Service access code: 335388)



**For emergencies involving the transport of dangerous goods;** 24/7 serviceCANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

**409B-140G**
**(AEROSOL)**
**Section 2: Hazard(s) Identification**
**Classification of Hazardous Chemical**
**GHS Categories**

Criteria	Category	Signal Word	Pictograms
Flammable Aerosol	1	Danger	Flame
Aspiration Hazard	1	Danger	Health
Specific Target Organ Toxicity Repeated Exposure	1	Danger	Health
Reproductive Toxicity	2	Warning	Health
Skin Irritation	2	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation
Hazardous to Aquatic Environment Chronic	3	none	none



*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>DANGER</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H222: Extremely Flammable aerosol H229: Pressurized container: may burst if heated
	H304: May be fatal if swallowed and enters airways H361: Suspected of damaging fertility or the unborn child H372: Causes damage to organs (central nervous system) through prolonged or repeated exposure

*Section continued on the next page*

**409B-140G****(AEROSOL)***Continued...*

<b>Pictograms</b>	<b>Hazard Statements</b>
	H315: Causes skin irritation H336: May cause drowsiness and dizziness
	H411: Toxic to aquatic life with long lasting effects
<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P201, P202	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist, vapors, and spray.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, and eye protection.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.

*Section continued on the next page*

**409B-140G**
**(AEROSOL)**

Continued...

<b>Response</b>	<b>Precautionary Statements</b>
P308 + P313	IF exposed or concerned: Get medical advice.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331	Do NOT induce vomiting.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER or doctor if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty water.
P332 + P313	If skin irritation occurs: Get medical advice.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
<b>Storage</b>	<b>Precautionary Statements</b>
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents in accordance to local, regional, and national regulations.

**Hazards Not Otherwise Classified**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None
Simple Asphyxiant	May displace oxygen and cause rapid suffocation.	Warning	None

**409B-140G**
**(AEROSOL)**
**Section 3: Composition/Information on Ingredients**

CAS #	Chemical Name	%(weight)
107-83-5	methyl-2-pentane	30-38%
811-97-2	1,1,1,2-tetrafluoroethane <sup>a)</sup>	25%
96-14-0	methyl-3-pentane	11-15%
79-29-8	dimethyl-2,3-butane	11-15%
75-83-2	dimethyl-2,2-butane	7-11%
109-66-0	pentane	4-8%
110-54-3	n-hexane	1-5%

a) Also known as HFC-134a

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
<b>IF SWALLOWED</b>	P301 + P310, P331, P308 + P313
<b>Immediate Symptoms</b>	<i>nausea, weakness, headache, abdominal pain, drowsiness, dizziness, unconsciousness</i>
<b>Response</b>	Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF exposed or concerned: Get medical advice.
<b>IF INHALED</b>	P304 + P340, P312
<b>Immediate Symptoms</b>	<i>nausea, weakness, headache, drowsiness, dizziness, unconsciousness</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
<b>IF ON SKIN</b>	P302 + P352, P332 + P313, P362 + P364
<b>Immediate Symptoms</b>	<i>dry skin, redness, irritation</i>
<b>Response</b>	Wash with plenty of water. If skin irritation occurs: Get medical advice. Take off contaminated clothing and wash it before reuse.

Section continued on the next page

**409B-140G****(AEROSOL)**

Continued...

<b>IF IN EYES</b>	P305 + P351 + P338
<b>Immediate Symptoms</b>	<i>low toxicity: redness</i>
<b>Response</b>	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.  Use water spray to cool containers.
<b>Specific Hazards</b>	Aerosols containers may erupt with force at temperatures above 50 °C [122 °F].  Produces irritating and toxic fumes in fires or in contact with hot surfaces.  The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.  Prevent fire-fighting wash from entering waterway or sewer system.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ), halogenated compounds, and hydrogen fluorides.
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Do not breathe the mist, spray and vapors. Remove or keep away all sources of extreme heat or open flames.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Not applicable
<b>Cleaning Methods</b>	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**409B-140G**
**(AEROSOL)**
**Section 7: Handling and Storage**
**Prevention**

Keep out of reach of children.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not breathe mist, vapors, and spray. Use only outdoors or in a well-ventilated area.

Do not pierce or burn, even after use.

**Handling**

Do not spray on an open flame or other ignition source.

Wear protective gloves and eye protection. Take off contaminated clothing and wash it before reuse.

Wash hands thoroughly after handling.

Avoid release to the environment.

**Storage**

Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].

Store in a well-ventilated place.

Store locked up.

**Section 8: Exposure Controls/Personal Protection**
**Substances with Occupational Exposure Limit Values**

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
1,1,1,2-tetrafluoroethane	MG Chemicals <sup>a)</sup> ACGIH U.S.A. OSHA PEL Canada	1 000 ppm Not established Not established Not established	Not established Not established Not established Not established
methyl-2-pentane Hexane isomers (except n-Hexane)	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm (500 ppm) <sup>b)</sup> 500 ppm 200 ppm 500 ppm 500 ppm	1 000 ppm (1 000 ppm) <sup>b)</sup> 1 000 ppm Not established 1 000 ppm 1 000 ppm

Section continued on the next page

**409B-140G**
**(AEROSOL)**
*Continued...*

<b>Chemical Name</b>	<b>Country/ Provinces</b>	<b>Long Term Exposure Limits (PEL)</b>	<b>Short Term Exposure Limits (STEL)</b>
methyl-3-pentane <i>Hexane isomers (except n-Hexane)</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm (500 ppm) <sup>b)</sup> 500 ppm 200 ppm 500 ppm 500 ppm	1 000 ppm (1 000 ppm) <sup>b)</sup> 1 000 ppm Not established 1 000 ppm 1 000 ppm
dimethyl-2,3-butane <i>Hexane isomers (except n-Hexane)</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm (500 ppm) <sup>b)</sup> 500 ppm 200 ppm 500 ppm 500 ppm	1 000 ppm (1 000 ppm) <sup>b)</sup> 1 000 ppm Not established 1 000 ppm 1 000 ppm
dimethyl-2,2-butane <i>Hexane isomers (except n-Hexane)</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm (500 ppm) <sup>b)</sup> 500 ppm 200 ppm 500 ppm 500 ppm	1 000 ppm (1 000 ppm) <sup>b)</sup> 1 000 ppm Not established 1 000 ppm 1 000 ppm
pentane	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	1000 ppm 1000 ppm 600 ppm 600 ppm 600 ppm 120 ppm	Not established Not established Not established Not established 750 ppm Not established
n-hexane	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	50 ppm 50 ppm 50 ppm 50 ppm 50 ppm 50 ppm	Not established Not established Not established Not established Not established Not established

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) MG Chemicals recommended limit corresponding to prevalent international threshold values

b) Value vacated (retracted) under court order, but still in effect in some states.

*Section continued on the next page*

**409B-140G****(AEROSOL)****Engineering Controls**

**Ventilation** Keep airborne concentrations below the occupational exposure limits (OEL).

**Personal Protective Equipment**

**Eye protection** Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Ensure that glasses have side shields for lateral protection.

**Skin Protection** For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

**Respiratory Protection** For over-exposures up to 10 x OEL of mist, vapors, and spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

**409B-140G**
**(AEROSOL)**
**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid, in an aerosol format	<b>Lower Flammability Limit</b>	1%
<b>Appearance</b>	Colorless	<b>Upper Flammability Limit</b>	7%
<b>Odor</b>	Starting fluid petroleum	<b>Vapor Pressure @20 °C</b>	33 kPa [250 mmHg]
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	2.98 (Air =1)
<b>pH</b>	Not available	<b>Relative Density @15.5 °C</b>	0.66
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Immiscible
<b>Initial Boiling Point</b>	52 °C [125 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point</b> <sup>a)</sup>	-29 °C [-20 °F]	<b>Auto-ignition Temperature</b>	Not available
<b>Evaporation Rate</b>	0.8 (Ether = 1)	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Extremely Flammable	<b>Viscosity @40 °C</b>	<20.5 mm <sup>2</sup> /s

a) Closed cup flash point

**Section 10: Stability and Reactivity**

<b>Reactivity</b>	Not available
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Temperatures above 50 °C [122 °F], open flames, and incompatible substances
<b>Incompatibilities</b>	Strong oxidizing agents, alkali or alkali earth metals, powdered aluminum, zinc, magnesium, and beryllium
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

**409B-140G**
**(AEROSOL)**
**Section 11: Toxicological Information**
**Summary of Effects and Symptoms by Routes of Exposure**

<b>Eyes</b>	Low toxicity: may cause redness.
<b>Inhalation</b>	May cause nausea, weakness, headache, drowsiness, dizziness, and unconsciousness.
<b>Ingestion</b>	May cause nausea, weakness, headache, abdominal pain, drowsiness, dizziness, and unconsciousness (also see inhalation symptoms).
<b>Skin</b>	May cause dry skin, redness, and irritation.
<b>Chronic</b>	Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin.  Ingestion or inhalation of paint material, mist, or vapor during pregnancy may increase the chances fetal death and developmental defects.

**Acute Toxicity (Lethal Exposure Concentrations)**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
1,1,1,2-tetrafluoroethane	Not available	Not available	1 500 g/m <sup>3</sup> 4 h Rat (gas)
methyl-2-pentane	Not available	Not available	3 125 ppm Rat
methyl-3-pentane	Not available	Not available	Not available
dimethyl-2,3-butane	Not available	Not available	Not available
dimethyl-2,2-butane	Not available	Not available	Not available
pentane	>2 000 mg/kg Rat	Not available	23.5 mg/L 4 h Rat
n-hexane	15 840 mg/kg Rat	2 000 mg/kg Rabbit <sup>b)</sup>	48 000 ppm 4 h Rat
ATE	>2 000 mg/kg	>2 000 mg/kg	>10 g/m <sup>3</sup>

*Note:* Toxicity data from the ECHA database were consulted. The data from supplier SDS were also consulted.

*Section continued on the next page*

**409B-140G****(AEROSOL)****Other Toxicological Effects**

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/irritation</b>	Based on available data, the classification criteria are not met.
<b>Sensitization</b> (allergic reactions)	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b> (risk of cancer)	Based on available data, the classification criteria are not met.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Based on available data, the classification criteria are not met.
<b>Teratogenicity</b> (risk of fetus malformation)	The n-hexane component causes harm to fetus according to animal studies.
<b>STOT-single exposure</b>	The hexane isomers may affect the central nervous system.
<b>STOT-repeated exposure</b>	The n-hexane component cause harm to the central nervous system.
<b>Aspiration hazard</b>	Mixture is a class 1 aspiration hazard. It contain 75% class 1 aspiration hazard components and has a mixture viscosity of <math><20.5 \text{ mm}^2/\text{s}</math> at 40 °C.

**409B-140G****(AEROSOL)****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Similar mixtures of isoalkanes C6-C7 with <5% n-hexane have a LC50 96 h of 11.4 mg/L for rainbow trout (*Oncorhynchus mykiss*), and an EL50 48 h of 3.0 mg/L water flea (*Daphnia magna*).

**Acute Ecotoxicity**

See chronic ecotoxicity.

**Chronic Ecotoxicity**

Category 3

Harmful to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

**Biodegradability**

Not available

**Other Effects**

Actual VOC (Volatile Organic Compounds) content according to the US (EPA) and Canadian (CEPA) authorities = 75% [495 g/L]

Note: The VOC exemption for 1,1-difluoroethane was applied.

**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, and national regulations.

**409B-140G**

**(AEROSOL)**


**Section 14: Transport Information**

**Ground**

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);  
**USA CFR 49 Regulations** (Parts 100 to 185).

**Limited Quantity**

Max Net Qty/Pkg  
30 kg G



**Air**

**Refer to ICAO-IATA Dangerous Goods Regulations.**

**Limited Quantity**

See package  
instruction Y203

Max Net Qty/Pkg  
30 kg G



**UN number:** UN1950

**Shipping Name:** AEROSOL,  
flammable

**Class:** 2.1

**Packing Group:** Not applicable

**Marine Pollutant:** Yes

**Sea**

**Refer to IMDG regulations.**

**Limited Quantity**

Max Net Qty/Pkg  
30 kg G



**UN number:** UN1950

**Shipping Name:** AEROSOL,  
flammable

**Class:** 2.1

**Packing Group:** Not applicable

**Marine Pollutant:** Yes

**Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

**409B-140G**

**(AEROSOL)**

**Section 15: Regulatory Information**

**Canada**

**Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2023.

**USA**

**OSHA Hazard Communication Standard (29 CFR Part 1900)**


The safety data sheet and label comply with HCS 2024.

**Other Classifications**

**HMIS® RATING**

<b>HEALTH:</b>	<b>* 2</b>
<b>FLAMMABILITY:</b>	<b>3</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

**NFPA® 704 CODES**



*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain products that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains ≤5% n-hexane (CAS# 110-54-3; reportable quantity = 5 000 lb), which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372

*Section continued on the next page*

**409B-140G****(AEROSOL)****TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity).

This product contains n-hexane, which is listed as reproductively toxic.

**Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**Section 16: Other Information**

<b>SDS Prepared by</b>	MG Chemicals' Regulatory department
<b>Date of Review</b>	6 February 2025
<b>Supersedes</b>	14 April 2024
<b>Reason for Changes:</b>	Update to WHMIS 2023 and HCS 2024

**Reference**

1) ACGIH 2023 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2023).

*Section continued on the next page*

**409B-140G****(AEROSOL)****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

Phone: +1-905-331-1396

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

**Disclaimer** This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.

409B-340G

(AEROSOL)

# aSafety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Identifier:** 409B-340G**Other Means Of Identification:** Electrosolve™ Contact Cleaner**Related Part #** 409B-340G

### Recommended Use and Restriction on Use

**Use:** Zero-residue contact cleaner**Uses Advised Against:** Do not use on live circuits or in presence of ignition source

### Details of Manufacturer or Importer

**Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADA**Distributor**Mouser Electronic  
1000 North Main Street  
Mansfield, TX 76063  
USA

☎ +1-905-331-1396

+1 800-340-0772

**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number

**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**

(Service access code: 335388)



**For emergencies involving the transport of dangerous goods;** 24/7 serviceCANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

**409B-340G**
**(AEROSOL)**
**Section 2: Hazard(s) Identification**
**Classification of Hazardous Chemical**
**GHS Categories**

Criteria	Category	Signal Word	Pictograms
Flammable Aerosol	1	Danger	Flame
Aspiration Hazard	1	Danger	Health
Specific Target Organ Toxicity      Repeated Exposure	1	Danger	Health
Reproductive Toxicity	2	Warning	Health
Skin Irritation	2	Warning	Exclamation
Specific Target Organ Toxicity      Single Exposure	3	Warning	Exclamation
Hazardous to Aquatic Environment      Chronic	3	none	none



*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>DANGER</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H222: Extremely Flammable aerosol H229: Pressurized container: may burst if heated
	H304: May be fatal if swallowed and enters airways H361: Suspected of damaging fertility or the unborn child H372: Causes damage to organs (central nervous system) through prolonged or repeated exposure

*Section continued on the next page*

**409B-340G****(AEROSOL)***Continued...*

<b>Pictograms</b>	<b>Hazard Statements</b>
	H315: Causes skin irritation H336: May cause drowsiness and dizziness
	H411: Toxic to aquatic life with long lasting effects
<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P201, P202	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist, vapors, and spray.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, and eye protection.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.

*Section continued on the next page*

**409B-340G**
**(AEROSOL)**

Continued...

<b>Response</b>	<b>Precautionary Statements</b>
P308 + P313	IF exposed or concerned: Get medical advice.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331	Do NOT induce vomiting.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER or doctor if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty water.
P332 + P313	If skin irritation occurs: Get medical advice.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
<b>Storage</b>	<b>Precautionary Statements</b>
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents in accordance to local, regional, and national regulations.

**Hazards Not Otherwise Classified**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None
Simple Asphyxiant	May displace oxygen and cause rapid suffocation.	Warning	None

**409B-340G**
**(AEROSOL)**
**Section 3: Composition/Information on Ingredients**

CAS #	Chemical Name	%(weight)
107-83-5	methyl-2-pentane	30-38%
75-37-6	1,1-difluoroethane <sup>a)</sup>	25%
96-14-0	methyl-3-pentane	11-15%
79-29-8	dimethyl-2,3-butane	11-15%
75-83-2	dimethyl-2,2-butane	7-11%
109-66-0	pentane	4-8%
110-54-3	n-hexane	1-5%

a) Also known as HFC-152a

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
<b>IF SWALLOWED</b>	P301 + P310, P331, P308 + P313
<b>Immediate Symptoms</b>	<i>nausea, weakness, headache, abdominal pain, drowsiness, dizziness, unconsciousness</i>
<b>Response</b>	Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF exposed or concerned: Get medical advice.
<b>IF INHALED</b>	P304 + P340, P312
<b>Immediate Symptoms</b>	<i>nausea, weakness, headache, drowsiness, dizziness, unconsciousness</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
<b>IF ON SKIN</b>	P302 + P352, P332 + P313, P362 + P364
<b>Immediate Symptoms</b>	<i>dry skin, redness, irritation</i>
<b>Response</b>	Wash with plenty of water. If skin irritation occurs: Get medical advice. Take off contaminated clothing and wash it before reuse.

*Section continued on the next page*

**409B-340G****(AEROSOL)**

Continued...

<b>IF IN EYES</b>	P305 + P351 + P338
<b>Immediate Symptoms</b>	<i>low toxicity: redness</i>
<b>Response</b>	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

### Section 5: Fire-Fighting Measures

<b>Extinguishing Media</b>	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.  Use water spray to cool containers.
<b>Specific Hazards</b>	Aerosols containers may erupt with force at temperatures above 50 °C [122 °F].  Produces irritating and toxic fumes in fires or in contact with hot surfaces.  The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.  Prevent fire-fighting wash from entering waterway or sewer system.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ), halogenated compounds, and hydrogen fluorides.
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

### Section 6: Accidental Release Measures

<b>Personal Protection</b>	See personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Do not breathe the mist, spray and vapors. Remove or keep away all sources of extreme heat or open flames.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Not applicable
<b>Cleaning Methods</b>	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**409B-340G**
**(AEROSOL)**
**Section 7: Handling and Storage**
**Prevention**

Keep out of reach of children.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not breathe mist, vapors, and spray. Use only outdoors or in a well-ventilated area.

Do not pierce or burn, even after use.

**Handling**

Do not spray on an open flame or other ignition source.

Wear protective gloves and eye protection. Take off contaminated clothing and wash it before reuse.

Wash hands thoroughly after handling.

Avoid release to the environment.

**Storage**

Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].

Store in a well-ventilated place.

Store locked up.

**Section 8: Exposure Controls/Personal Protection**
**Substances with Occupational Exposure Limit Values**

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
1,1-difluoroethane	MG Chemicals <sup>a)</sup> ACGIH U.S.A. OSHA PEL Canada	1 000 ppm Not established Not established Not established	Not established Not established Not established Not established
methyl-2-pentane Hexane isomers (except n-Hexane)	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm (500 ppm) <sup>b)</sup> 500 ppm 200 ppm 500 ppm 500 ppm	1 000 ppm (1 000 ppm) <sup>b)</sup> 1 000 ppm Not established 1 000 ppm 1 000 ppm

*Section continued on the next page*

**409B-340G**
**(AEROSOL)**
*Continued...*

<b>Chemical Name</b>	<b>Country/ Provinces</b>	<b>Long Term Exposure Limits (PEL)</b>	<b>Short Term Exposure Limits (STEL)</b>
methyl-3-pentane <i>Hexane isomers (except n-Hexane)</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm (500 ppm) <sup>b)</sup> 500 ppm 200 ppm 500 ppm 500 ppm	1 000 ppm (1 000 ppm) <sup>b)</sup> 1 000 ppm Not established 1 000 ppm 1 000 ppm
dimethyl-2,3-butane <i>Hexane isomers (except n-Hexane)</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm (500 ppm) <sup>b)</sup> 500 ppm 200 ppm 500 ppm 500 ppm	1 000 ppm (1 000 ppm) <sup>b)</sup> 1 000 ppm Not established 1 000 ppm 1 000 ppm
dimethyl-2,2-butane <i>Hexane isomers (except n-Hexane)</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm (500 ppm) <sup>b)</sup> 500 ppm 200 ppm 500 ppm 500 ppm	1 000 ppm (1 000 ppm) <sup>b)</sup> 1 000 ppm Not established 1 000 ppm 1 000 ppm
pentane	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	1000 ppm 1000 ppm 600 ppm 600 ppm 600 ppm 120 ppm	Not established Not established Not established Not established 750 ppm Not established
n-hexane	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	50 ppm 50 ppm 50 ppm 50 ppm 50 ppm 50 ppm	Not established Not established Not established Not established Not established Not established

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) MG Chemicals recommended limit corresponding to prevalent international threshold values

b) Value vacated (retracted) under court order, but still in effect in some states.

*Section continued on the next page*

**409B-340G****(AEROSOL)****Engineering Controls**

**Ventilation** Keep airborne concentrations below the occupational exposure limits (OEL).

**Personal Protective Equipment**

**Eye protection** Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Ensure that glasses have side shields for lateral protection.

**Skin Protection** For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

**Respiratory Protection** For over-exposures up to 10 x OEL of mist, vapors, and spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

**409B-340G**
**(AEROSOL)**
**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid, in an aerosol format	<b>Lower Flammability Limit</b>	1%
<b>Appearance</b>	Colorless	<b>Upper Flammability Limit</b>	7%
<b>Odor</b>	Starting fluid petroleum	<b>Vapor Pressure @20 °C</b>	33 kPa [250 mmHg]
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	2.98 (Air =1)
<b>pH</b>	Not available	<b>Relative Density @15.5 °C</b>	0.66
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Immiscible
<b>Initial Boiling Point</b>	52 °C [125 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point</b> <sup>a)</sup>	-29 °C [-20 °F]	<b>Auto-ignition Temperature</b>	Not available
<b>Evaporation Rate</b>	0.8 (Ether = 1)	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Extremely Flammable	<b>Viscosity @40 °C</b>	<20.5 mm <sup>2</sup> /s

a) Closed cup flash point

**Section 10: Stability and Reactivity**

<b>Reactivity</b>	Not available
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Temperatures above 50 °C [122 °F], open flames, and incompatible substances
<b>Incompatibilities</b>	Strong oxidizing agents, alkali or alkali earth metals, powdered aluminum, zinc, magnesium, and beryllium
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

**409B-340G**
**(AEROSOL)**
**Section 11: Toxicological Information**
**Summary of Effects and Symptoms by Routes of Exposure**

<b>Eyes</b>	Low toxicity: may cause redness.
<b>Inhalation</b>	May cause nausea, weakness, headache, drowsiness, dizziness, and unconsciousness.
<b>Ingestion</b>	May cause nausea, weakness, headache, abdominal pain, drowsiness, dizziness, and unconsciousness (also see inhalation symptoms).
<b>Skin</b>	May cause dry skin, redness, and irritation.
<b>Chronic</b>	Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin.  Ingestion or inhalation of paint material, mist, or vapor during pregnancy may increase the chances fetal death and developmental defects.

**Acute Toxicity (Lethal Exposure Concentrations)**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
1,1-difluoroethane	Not available	Not available	977 g/m <sup>3</sup> 4 h Rat
methyl-2-pentane	Not available	Not available	3 125 ppm Rat
methyl-3-pentane	Not available	Not available	Not available
dimethyl-2,3-butane	Not available	Not available	Not available
dimethyl-2,2-butane	Not available	Not available	Not available
pentane	>2 000 mg/kg Rat	Not available	23.5 mg/L 4 h Rat
n-hexane	15 840 mg/kg Rat	2 000 mg/kg Rabbit <sup>b)</sup>	48 000 ppm 4 h Rat
ATE	>2 000 mg/kg	>2 000 mg/kg	>10 g/m <sup>3</sup>

*Note:* Toxicity data from the ECHA database were consulted. The data from supplier SDS were also consulted.

*Section continued on the next page*

**409B-340G****(AEROSOL)****Other Toxicological Effects**

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/irritation</b>	Based on available data, the classification criteria are not met.
<b>Sensitization</b> (allergic reactions)	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b> (risk of cancer)	Based on available data, the classification criteria are not met.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Based on available data, the classification criteria are not met.
<b>Teratogenicity</b> (risk of fetus malformation)	The n-hexane component causes harm to fetus according to animal studies.
<b>STOT-single exposure</b>	The hexane isomers may affect the central nervous system.
<b>STOT-repeated exposure</b>	The n-hexane component cause harm to the central nervous system.
<b>Aspiration hazard</b>	Mixture is a class 1 aspiration hazard. It contain 75% class 1 aspiration hazard components and has a mixture viscosity of <math><20.5 \text{ mm}^2/\text{s}</math> at 40 °C.

**409B-340G****(AEROSOL)****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Similar mixtures of isoalkanes C6-C7 with <5% n-hexane have a LC50 96 h of 11.4 mg/L for rainbow trout (*Oncorhynchus mykiss*), and an EL50 48 h of 3.0 mg/L water flea (*Daphnia magna*).

**Acute Ecotoxicity**

See chronic ecotoxicity.

**Chronic Ecotoxicity**

Category 3

Harmful to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

**Biodegradability**

Not available

**Other Effects**

Actual VOC (Volatile Organic Compounds) content according to the US (EPA) and Canadian (CEPA) authorities = 75% [495 g/L]

Note: The VOC exemption for 1,1-difluoroethane was applied.

**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, and national regulations.

**409B-340G**

**(AEROSOL)**

**Section 14: Transport Information**

**Ground**

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);  
**USA CFR 49 Regulations** (Parts 100 to 185).

**Limited Quantity**

Max Net Qty/Pkg  
30 kg G



**Air**

**Refer to ICAO-IATA Dangerous Goods Regulations.**

**Limited Quantity**

See package  
instruction Y203

Max Net Qty/Pkg  
30 kg G



**UN number:** UN1950

**Shipping Name:** AEROSOL,  
flammable

**Class:** 2.1

**Packing Group:** Not applicable

**Marine Pollutant:** Yes

**Sea**

**Refer to IMDG regulations.**

**Limited Quantity**

Max Net Qty/Pkg  
30 kg G



**UN number:** UN1950

**Shipping Name:** AEROSOL,  
flammable

**Class:** 2.1

**Packing Group:** Not applicable

**Marine Pollutant:** Yes

**Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

**Section 15: Regulatory Information**

**Canada**

**Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2023.

**USA**

**OSHA Hazard Communication Standard (29 CFR Part 1900)**


The safety data sheet and label comply with HCS 2024.

**Other Classifications**

**HMIS® RATING**

<b>HEALTH:</b>	* 2
<b>FLAMMABILITY:</b>	3
<b>PHYSICAL HAZARD:</b>	0
<b>PERSONAL PROTECTION:</b>	

**NFPA® 704 CODES**



*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain products that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains ≤5% n-hexane (CAS# 110-54-3; reportable quantity = 5 000 lb), which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372

*Section continued on the next page*

**409B-340G****(AEROSOL)****TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity).

This product contains n-hexane, which is listed as reproductively toxic.

**Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**Section 16: Other Information**

<b>SDS Prepared by</b>	MG Chemicals' Regulatory department
<b>Date of Review</b>	6 February 2025
<b>Supersedes</b>	14 April 2024
<b>Reason for Changes:</b>	Update to WHMIS 2023 and HCS 2024

**Reference**

1) ACGIH 2023 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2023).

*Section continued on the next page*

**409B-340G****(AEROSOL)****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

Phone: +1-905-331-1396

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

**Disclaimer** This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.