

ELAN-Tron® C 105 Hardener

Version 5

Revision Date 03/10/2016

Print Date 03/10/2016

SECTION 1. IDENTIFICATION

Product name : ELAN-Tron® C 105 Hardener

Manufacturer or supplier's details

Company : ELANTAS PDG, INC.
5200 North 2nd Street
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : www.elantas.com

E-mail address : Todd.Thomas@altana.com

Emergency telephone number : INFOTRAC - 1-800-535-5053

Recommended use of the chemical and restrictions on use

Recommended use : Electrical Insulation

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Skin corrosion : Category 1B

Serious eye damage : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 1A

Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lungs)

GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H350 May cause cancer.
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

ELAN-Tron® C 105 Hardener

Version 5

Revision Date 03/10/2016

Print Date 03/10/2016

Precautionary statements : **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P281 Use personal protective equipment as required.

Response:
 P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P363 Wash contaminated clothing before reuse.

Storage:
 P405 Store locked up.

Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 6 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Modified Aliphatic Amidoamine

Hazardous components

Component	CAS-No.	Concentration (%)
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6	>= 45 - < 46

ELAN-Tron® C 105 Hardener

Version 5

Revision Date 03/10/2016

Print Date 03/10/2016

Fatty acid amine	68953-36-6	>= 38 - < 39
Tetraethylenepentamine	112-57-2	>= 6 - < 7
Natural Diatomaceous Earth	61790-53-2	>= 5 - < 6
Triethylenetetramine	112-24-3	>= 0 - < 1
Crystalline silica	14808-60-7	>= 0 - < 1

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

ELAN-Tron® C 105 Hardener

Version 5

Revision Date 03/10/2016

Print Date 03/10/2016

- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

ELAN-Tron® C 105 Hardener

Version 5

Revision Date 03/10/2016

Print Date 03/10/2016

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable fraction)	2 mg/m ³	ACGIH
Tetraethylenepentamine	112-57-2	TWA	5 mg/m ³	US WEEL
Natural Diatomaceous Earth	61790-53-2	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m ³ (Silica)	NIOSH REL
		TWA	1 ppm	US WEEL
Crystalline silica	14808-60-7	TWA (total dust)	30 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable fraction)	0.025 mg/m ³ (Silica)	ACGIH

Engineering measures

- : Use with adequate ventilation.
 All application areas should be ventilated in accordance with applicable OSHA regulations. (29 CFR 1910.94)
 This product contains a particulate(s) that is considered hazardous per OSHA (29 CFR 1910.1200) and is listed in Section III as a precautionary warning.
 Under normal conditions of use, this product as supplied does not pose a health risk from particulate matter.
 Physical degradation of the cured product (i.e. sanding, abrading, etc.) may pose a dust hazard.
 Repeated inhalation of such dust may cause lung injury.

ELAN-Tron® C 105 Hardener

Version 5

Revision Date 03/10/2016

Print Date 03/10/2016

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Flash point : Greater than 201 °F (94 °C)
Method: No information available.
Information taken from reference works and the literature.
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available

ELAN-Tron® C 105 Hardener

Version 5

Revision Date 03/10/2016

Print Date 03/10/2016

Relative Density/Specific Gravity	:	No data available
Density	:	1.4679 g/cm ³ (77 °F (25 °C))
Solubility(ies) Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Thermal decomposition	:	No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Greater than 22 mm ² /s (104 °F (40 °C))

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	No data available
Hazardous decomposition products	:	Carbon monoxide in a fire. Nitrogen oxides in a fire. Ammonia

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eyes

Acute toxicity**Product:**

ELAN-Tron® C 105 Hardener

Version 5

Revision Date 03/10/2016

Print Date 03/10/2016

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:**112-57-2 Tetraethylenepentamine:**

Acute oral toxicity : LD50 Oral (Rat): 3,990 mg/kg

Acute dermal toxicity : LD50 (Rat): 660 mg/kg

112-24-3 Triethylenetetramine:

Acute oral toxicity : LD50 (Rat): 2,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 805 mg/kg

Skin corrosion/irritation**Product:**

Remarks: Extremely corrosive and destructive to tissue.

Components:**112-24-3 Triethylenetetramine:**

Method: OECD Test Guideline 435

Result: Corrosive

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Components:**112-24-3 Triethylenetetramine:**

Species: Rabbit

Result: Corrosive to eyes

Respiratory or skin sensitisation**Product:**

Remarks: Causes sensitisation.

Components:**112-24-3 Triethylenetetramine:**

Test Type: Buehler Test

Exposure routes: Dermal

Species: Guinea pig

ELAN-Tron® C 105 Hardener

Version 5

Revision Date 03/10/2016

Print Date 03/10/2016

Method: OECD Test Guideline 406
 Result: May cause sensitisation by skin contact.
 GLP: yes

Carcinogenicity

IARC	Group 1: Carcinogenic to humans	
	Crystalline silica	14808-60-7
ACGIH	Suspected human carcinogen	
	Crystalline silica	14808-60-7
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	
NTP	Known to be human carcinogen	
	Crystalline silica	14808-60-7

Further information
Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

ELAN-Tron® C 105 Hardener

Version 5

Revision Date 03/10/2016

Print Date 03/10/2016

Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste Code(s) : D002: Corrosive

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.**SECTION 14. TRANSPORT INFORMATION****International Regulation****IATA-DGR**UN/ID No. : UN 2735
Proper shipping name : Amines, liquid, corrosive, n.o.s.
(Tetraethylenepentamine, Triethylenetetramine)
Class : 8
Packing group : III
Labels : Corrosive
Packing instruction (cargo aircraft) : 856
Packing instruction (passenger aircraft) : 852**IMDG-Code**UN number : UN 2735
Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.
(Tetraethylenepentamine, Triethylenetetramine)
Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

ELAN-Tron® C 105 Hardener

Version 5

Revision Date 03/10/2016

Print Date 03/10/2016

National Regulations**49 CFR**

UN/ID/NA number : UN 2735
Proper shipping name : Amines, liquid, corrosive, n.o.s.
(Tetraethylenepentamine, Triethylenetetramine)
Class : 8
Packing group : III
Labels : Corrosive
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

ELAN-Tron® C 105 Hardener

Version 5

Revision Date 03/10/2016

Print Date 03/10/2016

Massachusetts Right To Know

Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6
Tetraethylenepentamine	112-57-2
Crystalline silica	14808-60-7

Pennsylvania Right To Know

Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6
Fatty acid amine	68953-36-6
Tetraethylenepentamine	112-57-2
Natural Diatomaceous Earth	61790-53-2

New Jersey Right To Know

Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6
Fatty acid amine	68953-36-6
Tetraethylenepentamine	112-57-2
Natural Diatomaceous Earth	61790-53-2
Chlorite	1318-59-8
Crystalline silica	14808-60-7

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : NOT APPLICABLE

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

Crystalline silica	14808-60-7
--------------------	------------

The components of this product are reported in the following inventories:

TSCA : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

Section 4 / 12(b) : Not applicable

Section 5 : Not applicable

DSL : We certify that all of the components of this product are listed on the DSL.

ELAN-Tron® C 105 Hardener

Version 5


Revision Date 03/10/2016

Print Date 03/10/2016

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	3*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 03/10/2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.