

824

(AEROSOL)

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Identifier:** 824**Other Means of Identification:** Isopropyl Alcohol Electronics Cleaner /  
Alcool Isopropylique, Nettoyant pour l'Électronique**Related Part #** 824-450G, 824-450GCA

### Recommended Use and Restriction on Use

**Use:** Cleaner for electronics**Uses Advised Against:** Not for use on monitor screens or glass with anti-glare coatings

### Details of Manufacturer or Importer

**Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADA**Distributor**Mouser Electronics  
1000 North Main Street  
Mansfield, TX 76063  
USA +1-905-331-1396**FAX** +1-800-340-0772**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number

**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)  
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**  
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service  
CANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

824

(AEROSOL)

**Section 2: Hazard(s) Identification**

**Classification of Hazardous Materials**

**GHS Categories**

Criteria	Category	Signal Word	Pictograms
Flammable Aerosol	2	Warning	Flame
Eye Irritation	2A	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity categories do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>WARNING</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H223: Flammable aerosol H229: Pressurized container: may burst if heated
	H319: Causes serious eye irritation H336: May cause drowsiness or dizziness

*Section continued on the next page*

**824**
**(AEROSOL)**
*Continued...*

<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing mist, vapors, and spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear eye protection.
P264	Wash hands thoroughly after handling.
<b>Response</b>	<b>Precautionary Statements</b>
P305 + P351 + P358	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P304+ P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER or doctor if you feel unwell.
<b>Storage</b>	<b>Precautionary Statements</b>
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
P403	Store in a well-ventilated place.
P405	Store locked up.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents and container in accordance to local, regional, and national regulations.

**Hazards Not Otherwise Classified**

<b>HCS2012 Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
Defats skin	Repeated exposure may cause skin dryness or cracking.	Not applicable	Not applicable
Simple Asphyxiant	May displace oxygen and cause rapid suffocation.	Warning	Not applicable

**824**
**(AEROSOL)**
**Section 3: Composition/Information on Ingredients**

CAS #	Chemical Name	%(weight)
67-63-0	propan-2-ol <sup>a)</sup>	75%
75-37-6	1,1-difluoroethane <sup>b)</sup>	25%

a) Commonly known as isopropyl alcohol (IPA)

b) Also known as HFC-152a

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
<b>IF IN EYES</b>	P305 + P351+ P338, P337 + P313
<b>Immediate Symptoms</b>	<i>redness, irritation, tearing</i>
<b>Response</b>	Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
<b>IF INHALED</b>	P304 + P340, P312
<b>Immediate Symptoms</b>	<i>dizziness, drowsiness, cough, headaches, weakness</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing. If feeling unwell: Call a POISON CENTRE or doctor.
<b>IF SWALLOWED</b>	P301 + P330, P331
<b>Immediate Symptoms</b>	<i>Low toxicity: nausea, headache, dizziness, drowsiness, weakness, abdominal pain, unconsciousness</i>
<b>Response</b>	Rinse mouth. Do NOT induce vomiting.
<b>IF ON SKIN</b>	P302 + P353
<b>Immediate Symptoms</b>	<i>Low toxicity: redness, dry skin, mild irritation</i>
<b>Response</b>	Rinse skin with water or shower.

824

**(AEROSOL)****Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	Use extinguishing media suitable for surrounding materials. Use water spray to cool containers.
<b>Specific Hazards</b>	Aerosols containers may erupt with force at temperatures above 50 °C [122 °F]. Produces irritating and toxic fumes in fires or in contact with hot surfaces. The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ) halogenated compounds, and hydrogen fluoride (HF).
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Avoid breathing the mist, spray, and vapors. Remove or keep away all sources of extreme heat or open flames.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Not applicable
<b>Cleaning Methods</b>	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue. <b>RECOMMENDATION:</b> Use a grounded stainless steel or carbon steel waste container.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**824**
**(AEROSOL)**
**Section 7: Handling and Storage**

<b>Prevention</b>	Keep out of reach from children.  Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.  Avoid breathing mist, spray, and vapors. Use only outdoors or in a well-ventilated area.
<b>Handling</b>	Wear eye protection.  Wash hands thoroughly after handling.
<b>Storage</b>	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].  Store in a well-ventilated place.  Store locked up.

**Section 8: Exposure Controls/Personal Protection**
**Substances with Occupational Exposure Limit Values**

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
propan-2-ol	ACGIH	200 ppm (TWA)	400 ppm
	U.S.A. OSHA PEL	400 ppm	Not established
	Canada AB	200 ppm	400 ppm
	Canada BC	200 ppm	400 ppm
	Canada ON	200 ppm	400 ppm
	Canada QC	400 ppm	500 ppm
1,1-difluoroethane	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada	Not established	Not established

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from suppliers' SDSs were also consulted. Short term exposure limits (STEL) are for 15 min and long-term permissible exposure limits (PEL) for 8 h.

*Section continued on the next page*

824

**(AEROSOL)****Engineering Controls**

**Ventilation** Keep airborne concentrations below the occupational exposure limits (OEL).

**Personal Protective Equipment**

**Eye protection** Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Use safety glasses with lateral protection (side shields).

**Skin Protection** For likely contacts, use of protective butyl rubber, nitrile, neoprene, polyethylene gloves or other chemically resistant gloves.

For incidental contacts, use disposable nitrile or neoprene gloves, or other chemically resistant gloves.

Do NOT use latex rubber, polyvinyl alcohol (PVA) or PVC gloves.

**Respiratory Protection** For over-exposures up to 10 x OEL of mist, vapors, and spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

**824**
**(AEROSOL)**
**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid in aerosol format	<b>Lower Flammability Limit</b>	2%
<b>Appearance</b>	Colorless	<b>Upper Flammability Limit</b>	12%
<b>Odor</b>	Alcohol-like	<b>Vapor Pressure @20 °C</b>	4.2 kPa [32 mmHg]
<b>Odor Threshold</b>	0.44 ppm	<b>Vapor Density</b>	≥1.6 (Air =1)
<b>pH</b>	Not available	<b>Relative Density @25 °C</b>	0.785
<b>Freezing/Melting Point</b>	-88 °C [-126 °F]	<b>Solubility in Water</b>	Fully miscible
<b>Initial Boiling Point</b>	≥81.8 °C [≥179 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point <sup>a)</sup></b>	12 °C [54 °F]	<b>Auto-ignition Temperature</b>	425 °C [797 °F]
<b>Evaporation Rate</b>	1.5 (ButAc = 1)	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Flammable	<b>Viscosity @20 °C</b>	2.4 mPa·s [3.1 mm <sup>2</sup> /s]

Note: Data for propan-2-ol liquid content without propellant

a) Closed cup value

**824**
**(AEROSOL)**
**Section 10: Stability and Reactivity**

<b>Reactivity</b>	At elevated temperatures, may react with aluminum and generate hydrogen gas.
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Temperatures above 50 °C [122 °F], open flames, and incompatible substances
<b>Incompatibilities</b>	Strong oxidizing agents, strong acids, alkali and alkali earth metals, halogenated compounds, aluminum at temperatures $\geq 49$ °C [ $\geq 120$ °F]
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

**Section 11: Toxicological Information**
**Summary of Effects and Symptoms by Routes of Exposure**

<b>Eyes</b>	Causes serious eye redness, irritation, or tearing.
<b>Skin</b>	May cause redness, dry skin, mild irritation.
<b>Inhalation</b>	May cause drowsiness or dizziness. Excessive exposure may cause cough, headaches, weakness, and unconsciousness.
<b>Ingestion</b>	May be harmful if swallowed. See inhalation symptoms.
<b>Chronic</b>	Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.

**Acute Toxicity (Lethal Exposure Concentrations)**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
isopropyl alcohol	5 840 mg/kg Rat	12 800 mg/kg Rabbit	16 000 ppm 8 h Rat
1,1-difluoroethane	Not available	Not available	1 500 g/m <sup>3</sup> 4 h Rat

*Note:* Toxicity data from the ECHA database were consulted. The data from supplier SDSs were also consulted.

*Section continued on the next page*

**824****(AEROSOL)**

<b>Skin corrosion/irritation</b>	Based on available data, the classification criteria are not met. Propan-2-ol causes mild skin irritation based on Draize tests on rabbits.
<b>Serious eye damage/irritation</b>	Propan-2-ol causes moderate to severe eye irritation based on Draize tests on rabbits
<b>Sensitization</b> (allergic reactions)	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b> (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Based on available data, the classification criteria are not met.
<b>Teratogenicity</b> (risk of fetus malformation)	Based on available data, the classification criteria are not met.
<b>STOT-single exposure</b>	Propan-2-ol can affect the central nervous system by inhalation causing drowsiness or dizziness.
<b>STOT-repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met. There are no category 1 components.

824

**(AEROSOL)****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Based on available data, propan-2-ol are not classifiable as toxic for the aquatic environment a minimal LC50 and EC50 >100 mg/L.

- Propan-2-ol is readily biodegradable and has a minimal LC50 96 h of 9 640 mg/L for Pimephales promelas (fathead minnow); an EC50 24 h of 5 102 mg/L Daphnia magna (water flea); and an EC50 72 h of >2 000 mg/L Desmodesmus subspicatus (green algae).

**Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds.

**Chronic Ecotoxicity**

Available toxicity data does not meet classification thresholds.

**Biodegradability**

The constituents are volatile and readily biodegradable.

**Other Effects****Volatile Organic Compound**


Actual Volatile Organic Content (VOC) = 75% (785 g/L)

**Global Warming Potential**

The propellant, HFC-152a, has a 100-year global warming potential of 124.

**Section 13: Disposal Considerations**

Dispose of contents in accordance with all local, regional, and national regulations.

**824****(AEROSOL)****Section 14: Transport Information****Ground****Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);  
**USA DOT 49 CFR** (Parts 100 to 185) **Regulations.****Limited Quantity****UN number:** UN1950  
**Shipping Name:** AEROSOL,  
flammable  
**Class:** 2.1  
**Packing Group:** Not applicable  
**Marine Pollutant:** No**Air****Refer to ICAO-IATA Dangerous Goods Regulations.****Limited Quantity**  
Max Net Qty/Pkg =  
30 kg Gross**UN number:** UN1950  
**Shipping Name:** AEROSOL,  
flammable  
**Class:** 2.1  
**Packing Group:** Not applicable  
**Marine Pollutant:** No**Sea****Refer to IMDG regulations.****Limited Quantity****UN number:** UN1950  
**Shipping Name:** AEROSOL,  
flammable  
**Class:** 2.1  
**Packing Group:** Not applicable  
**Marine Pollutant:** No**Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

824

(AEROSOL)

**Section 15: Regulatory Information**

**Canada**

**Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL/NDSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2023.

**USA**

**OSHA Hazard Communication Standard (29 CFR Part 1900)**


The safety data sheet and label comply with HCS 2024.

**Other Classifications**

**HMIS® RATING**

<b>HEALTH:</b>	<b>1</b>
<b>FLAMMABILITY:</b>	<b>3</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

**NFPA® 704 CODES**



*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains 75% propan-2-ol (CAS # 67-63-0) which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

*Section continued on the next page*

**824****(AEROSOL)****California Proposition 65**

(Chemicals known to cause cancer or reproductive toxicity, USA)

This product does not contain any substances known to be listed in California.

**Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

**Section 16: Other Information****SDS Prepared by** MG Chemicals' Regulatory Department**Date of Revision** 3 January 2025**Supersedes** 30 Octobre 2024**Reason for Changes:** Update to HCS 2024**References**

- 1) ACGIH 2023 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2023).

*Section continued on the next page*

**824****(AEROSOL)****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
NOELR	No observable effect loading ratio
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

Phone: +1-905-331-1396

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

**Disclaimer** This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.