

# SAFETY DATA SHEET



## Sterling® 77X-010

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

### SECTION 1. IDENTIFICATION

Product name : Sterling® 77X-010

#### Manufacturer or supplier's details

Company : ELANTAS PDG, INC.  
5200 North 2nd Street  
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : [www.elantas.com](http://www.elantas.com)

E-mail address : Todd.Thomas@altana.com

Emergency telephone number : INFOTRAC - 1-800-535-5053

#### Recommended use of the chemical and restrictions on use

Recommended use : Electrical Insulation

Restrictions on use : Refer to Section 15 for any restrictions that may apply

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Germ cell mutagenicity : Category 1B

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2 (Kidney, Liver)

#### GHS Label element

Hazard pictograms :   

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

**Sterling® 77X-010**

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H340 May cause genetic defects.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure.

## Precautionary statements

**: Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ eye protection/ face protection.  
P281 Use personal protective equipment as required.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste

# SAFETY DATA SHEET



## Sterling® 77X-010

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Modified Alkyd Resin Solution

### Hazardous components

Component	CAS-No.	Concentration (%)
VM&P Naptha	8032-32-4	>= 21 - < 22
Solvent naphtha (petroleum), light aliphatic	64742-89-8	>= 19 - < 20
Stoddard Solvent (Mineral spirits)	8052-41-3	>= 10 - < 11
Xylene	1330-20-7	>= 9 - < 10
Ethylbenzene	100-41-4	>= 2 - < 3
Toluene	108-88-3	>= 0 - < 1

## SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.  
If unconscious place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

# SAFETY DATA SHEET



## Sterling® 77X-010

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.

# SAFETY DATA SHEET



## Sterling® 77X-010

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.  
No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
VM&P Naptha	8032-32-4	TWA	350 mg/m <sup>3</sup>	NIOSH REL
		C	1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
Solvent naphtha (petroleum), light aliphatic	64742-89-8	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	400 ppm 1,600 mg/m <sup>3</sup>	OSHA P0
Stoddard Solvent (Mineral spirits)	8052-41-3	TWA	100 ppm	ACGIH
		TWA	500 ppm 2,900 mg/m <sup>3</sup>	OSHA Z-1
		TWA	100 ppm 525 mg/m <sup>3</sup>	OSHA P0
Xylene	1330-20-7	TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
		STEL	150 ppm 655 mg/m <sup>3</sup>	OSHA P0
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
		STEL	100 ppm	ACGIH
		TWA	150 ppm	ACGIH
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH

# SAFETY DATA SHEET



## Sterling® 77X-010

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
		STEL	125 ppm 545 mg/m <sup>3</sup>	OSHA P0
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	100 ppm 375 mg/m <sup>3</sup>	OSHA P0
		STEL	150 ppm 560 mg/m <sup>3</sup>	OSHA P0

**Engineering measures** : Use with adequate ventilation.  
All application areas should be ventilated in accordance with applicable OSHA regulations. (29 CFR 1910.94)

### Personal protective equipment

Respiratory protection	: In the case of vapour formation use a respirator with an approved filter.
Hand protection	
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available

# SAFETY DATA SHEET



## Sterling® 77X-010

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

Initial boiling point and boiling range	: No data available
Flash point	: 93 °F (34 °C) Method: No information available.
Evaporation rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.8604 g/cm3 (77 °F (25 °C))
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: Greater than 22 mm <sup>2</sup> /s (104 °F (40 °C))

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.

**Sterling® 77X-010**

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Hazardous decomposition products : Carbon monoxide in a fire.

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation

Skin contact

Skin absorption

Eyes

**Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 30000 ppm  
Exposure time: 4 h  
Test atmosphere: gas  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

**Components:****8032-32-4 VM&P Naptha:**

Acute inhalation toxicity : LC50 (Rat): 3400 ppm  
Exposure time: 4 h

**8052-41-3 Stoddard Solvent (Mineral spirits):**

Acute oral toxicity : LD50 (Rat): > 6,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5,500 mg/m<sup>3</sup>  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg

**1330-20-7 Xylene:**

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5000 ppm  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

# SAFETY DATA SHEET



## Sterling® 77X-010

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

### **100-41-4 Ethylbenzene:**

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,510 mg/kg

### **108-88-3 Toluene:**

Acute oral toxicity : LD50 (Rat): 2,600 mg/kg

### **Skin corrosion/irritation**

#### **Product:**

Remarks: May cause skin irritation in susceptible persons.

#### **Components:**

##### **8052-41-3 Stoddard Solvent (Mineral spirits):**

Species: Rabbit

Result: Moderate skin irritation

##### **1330-20-7 Xylene:**

Species: Rabbit

Result: Moderate skin irritation

##### **100-41-4 Ethylbenzene:**

Species: Rabbit

Result: Moderate skin irritation

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks: May cause irreversible eye damage.

#### **Components:**

##### **8032-32-4 VM&P Naptha:**

Result: Moderate eye irritation

Exposure time: 0.25 h

Remarks: largely based on human evidence

##### **8052-41-3 Stoddard Solvent (Mineral spirits):**

Species: Rabbit

Result: Eye irritation

##### **1330-20-7 Xylene:**

Species: Rabbit

Result: Eye irritation

##### **100-41-4 Ethylbenzene:**

Species: Rabbit

Result: Moderate eye irritation

**Sterling® 77X-010**

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

**Respiratory or skin sensitisation****Carcinogenicity**

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans	
	Ethylbenzene	100-41-4
<b>ACGIH</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	
<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	
<b>NTP</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.	

**Further information****Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a

# SAFETY DATA SHEET



## Sterling® 77X-010

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

EPA Hazardous Waste Code(s) : D001: Ignitable  
D018: Benzene

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14. TRANSPORT INFORMATION

### International Regulation

#### IATA-DGR

UN/ID No. : UN 1866  
Proper shipping name : Resin solution  
Class : 3  
Packing group : III  
Labels : Flammable liquid  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

#### IMDG-Code

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# SAFETY DATA SHEET



## Sterling® 77X-010

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

### National Regulations

#### 49 CFR

UN/ID/NA number	:	UN 1866
Proper shipping name	:	Resin solution
Class	:	3
Packing group	:	III
Labels	:	Flammable liquid
ERG Code	:	127
Marine pollutant	:	no

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	1,095

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a SARA 302 RQ.

#### SARA 311/312 Hazards

- : Fire Hazard
- Acute Health Hazard
- Chronic Health Hazard

#### SARA 302

- : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313

- : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Xylene 1330-20-7 9.1 %

Ethylbenzene 100-41-4 2.5 %

#### Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Xylene	1330-20-7	9.1 %
Ethylbenzene	100-41-4	2.5 %

# SAFETY DATA SHEET



## Sterling® 77X-010

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

Xylene	1330-20-7	9.1 %
Ethylbenzene	100-41-4	2.5 %

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

### Massachusetts Right To Know

Stoddard Solvent (Mineral spirits)	8052-41-3
Xylene	1330-20-7
Ethylbenzene	100-41-4
Benzene	71-43-2

### Pennsylvania Right To Know

Alkyd resin	Not Assigned
VM&P Naptha	8032-32-4
Solvent naphtha (petroleum), light aliphatic	64742-89-8
Stoddard Solvent (Mineral spirits)	8052-41-3
Xylene	1330-20-7
Ethylbenzene	100-41-4
p-xylene	106-42-3
Toluene	108-88-3
Cumene	98-82-8

### New Jersey Right To Know

Alkyd resin	Not Assigned
VM&P Naptha	8032-32-4
Solvent naphtha (petroleum), light aliphatic	64742-89-8
Stoddard Solvent (Mineral spirits)	8052-41-3
Xylene	1330-20-7
Ethylbenzene	100-41-4
Toluene	108-88-3

**New Jersey Trade Secret** : NOT APPLICABLE  
**Registry Number for the product (NJ TSRN)**

### California Prop 65

Ethylbenzene	WARNING! This product contains a chemical known to the State of California to cause cancer.
Cumene	100-41-4
Benzene	98-82-8
Naphthalene	71-43-2

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

# SAFETY DATA SHEET



## Sterling® 77X-010

Version 4

Revision Date 06/09/2015

Print Date 06/10/2015

harm.  
Toluene 108-88-3  
Benzene 71-43-2

### The components of this product are reported in the following inventories:

TSCA : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720.30(h).

Section 4 / 12(b) : Not applicable


Section 5 : Not applicable

DSL : The following component(s) is/are not listed on the DSL:  
: Alkyd resin

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



#### HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

Revision Date : 06/09/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.